



BKCB-H1100S



BKCB-H1300S



BKCB-H1800S


## Horizontal Laminar Flow Cabinet



**LCD Display**  
7-inch color touch screen, real-time display of running status.



**Waterproof Socket**  
Optimum convenience of using small devices inside the cabinet.



**UV Lamp**  
Emission of 253.7 nanometers for most efficient decontamination. The radiation intensity is not less than 400mW/m<sup>2</sup>.



**Foot-master Caster**  
Universal aster with brake and leveling feet.

## ADVANTAGE

- Vertical face design, the operating perspective is wide and more humane;
- Made of high-quality cold rolled steel plate material, welding structure, surface electrostatic spraying, enhancing the stability of the cabinet;
- Equipped with pre-filter, which can preliminarily filter large particulate matter, thus improving the service life of HEPA filter;
- Work zone is made of SUS304 material, beautiful and corrosion resistance;
- The front and side Windows are made of 5mm thick tempered glass;
- The base stand and casters are integrated design, which can be moved safely through the casters and can also be fixed and leveled;
- 7-inch color touch screen, real-time display of running status (air flow direction, air velocity, running time, UV lamp time, HEPA filter running time, HEPA filter running resistance, temperature and humidity, timer);
- With the function of appointment timing, it can automatically set the time of starting and shutting down and the disinfection time of ultraviolet lamp;
- With one key disinfection function, convenient and fast;
- Perfect alarm system:
  - Ultra-high filter pressure alarm
  - Filter failure replacement alarm
- Interlocking function: UV lamp and front window; UV lamp and fan, fluorescent lamp; fan and front window.

## TECHNICAL PARAMETERS

Model	BKCB-H1100S	BKCB-H1300S	BKCB-H1800S
External Size(W*D*H)	1100*820*1780mm	1300*820*1780mm	1800*820*2070mm
Internal Size(W*D*H)	1000*500*570mm	1200*500*570mm	1700*500*570mm
Work Surface Height	750mm(Customized)		
Safety Height	200mm		
Max Opening	320mm		
Display	LCD display		
Airflow Velocity	0.2~0.45m/s		
Material	Working area: 304 stainless steel; Main body: 1.2mm cold-rolled steel with anti-bacteria powder coating; Front window: 5mm toughened glass, anti-UV.		
Pre-Filter	Polyester fiber		
HEPA Filter	One, 99.995% efficiency at 0.3µm		
Front Window	Manual		
Noise	≤65dB(A)		
Illumination	≥300lx		
Vibration	≤5µm(rms)		
Safety	Colonies Number ≤ 0.5CFU/30min		
Clean Level	ISO Level 5(Class 100)		
Waterproof Sockets	Two sockets, Max. Power: 500W		
Power Supply	AC220V±10%, 50/60Hz(Standard); 110V±10%, 60Hz(Optional)		
Consumption	1200W	1200W	2000W
LED Lamp	8W*1	8W*1	16W*1
UV Lamp	15W*1	15W*1	40W*1
Standard Accessories	Base stand; LED lamp; UV lamp; Waterproof socket*2.		
Optional Accessories	Motorized Door		
Package Size(W*D*H)	1250*1040*1620mm	1450*1040*1620mm	1950*1060*1600mm
Gross Weight	262kg	300kg	325kg