

Electric-heating Water Distiller



Features:

- * Anti-dry protection: Auto shut-off and audible alarm at low water level.
- * High-quality stainless steel body, corrosion-resistant with long service life.
- * Closed-type overflow with built-in water level observation window for real-time liquid level monitoring.
- * All-copper drain faucet, resistant to rust, and detachable.

Technical Parameters:

Model	BK-EWD5	BK-EWD5A	BK-EWD10	BK-EWD10A	BK-EWD20	BK-EWD20A
Water Output	5L/h		10L/h		20L/h	
Inlet Water Requirements	Tap water, drinking water					
Capacity(Pending Distilled Water)	9L		13.5L		27L	
Material	201 stainless steel					
Water Quality of Produced Water	≤10μS/cm					
Heating Method	Electric heating					
Anti-dry Protection	/	Standard	/	Standard	/	Standard
Power Supply	AC220V, 50Hz(Standard); AC110V, 60Hz(Optional)		AC380V, 50Hz(Standard)			
Consumption	4.5kW		7.5kW		13.5kW	
Product Size(W*D*H)	Φ250*710mm		Φ300*780mm		Φ350*1000mm	
Net Weight	4.5kg	5kg	6.5kg	7kg	9.5kg	10kg
External Size(W*D*H)	300*300*610mm		340*320*730mm		400*350*730mm	
Gross Weight	5.5kg	6kg	6.8kg	8.3kg	11kg	10.5kg

BIOBASE

E-mail: export@biobase.com
www.biobase.cc / www.biobase.com