



Horizontal Laminar Flow Cabinet



E-mail: export@biobase.com

www.biobase.cc / www.biobase.com



Temperature and Humidity Sensor



UV Lamp



LED Display
Digital LED Display:
Airflow Level



Footmaster Caster
Universal Caster with
Brake and Leveling Feet



Base Stand



Waterproof Socket

ADVANTAGE

1. The cabinet is designed with a 10° inclination angle, the operation perspective is wide and more humanized.
2. Made of high quality cold rolled steel plate material, welding structure, surface electrostatic spraying, enhancing the stability of the cabinet.
3. Equipped with initial effect filter, which can preliminarily filter large particulate matter, thus improving the service life of the high efficiency filter.
4. Work surface is made of high quality 304 stainless steel material, beautiful and corrosion resistance.
5. The base bracket and casters are integrated design, which can be moved safely through the casters and can also be fixed and leveled.
6. 7-inch color touch screen, real-time display of running status (air flow direction, air velocity, machine running time, UV lamp running time, high efficiency filter running time, high efficiency filter running resistance, operating area temperature and humidity, clock display) at a glance.
7. With the function of appointment timing, it can automatically set the time of starting and shutting down the laminar flow cabinet and the disinfection time of ultraviolet lamp.
8. With a key disinfection function, convenient and fast, greatly saving the work time and improving the work efficiency.
9. Perfect alarm system:
 - (1) Ultra-high filter pressure alarm: when the filter resistance increases, sound alarm will be issued.
 - (2) Filter failure replacement alarm: when the filter service life expires, there will be a filter replacement sound alarm.

TECHNICAL PARAMETERS

Model	BKCB-H1500	BKCB-H1800
Flow Mode	Horizontal Flow	
Number of Users	1~2	1~3
Rated Power	1250VA (including operating area socket load 500VA)	2000VA (including operating area socket load 500VA)
Power Supply	220V±10%, 50Hz (Standard); 110±10%V, 60Hz (Optional)	
Airflow Velocity	0.2m/s~0.45m/s	
Noise	≤65dB (A)	
Lighting	≥300lx	
Vibration	≤5μm(rms)	
Safety	Colonies Number ≤ 0.5CFU/30min	
Clean Grade	ISO Level 5 (100 levels)	
Filtration Efficiency	HEPA (H14) high efficiency filter, filtration efficiency for 0.3μm particle≥99.995%	
Work Surface Height	750mm(Customized)	
Standard Accessory	LED lamp*1, UV lamp*2, Base stand, Waterproof socket*2, Temperature and humidity sensor	
Optional Accessory	Armrest*2	
Net Weight	220kg	260kg
Gross Weight	299kg	355kg
External Size(W*D*H)	1500*800*1730mm	1800*800*1930mm
Internal Size(W*D*H)	1400*500*600mm	1700*500*730mm
Package Size(W*D*H)	1760*1010*1340mm	2060*1010*1500mm