

## Table Top High Speed Centrifuge



### Features for BKC-TH16II:

- \* DC Brushless motor with high start torque and frequency inversion for smooth running, maintenance-free.
- \* Microprocessor control, LED display, Memory flashing function, conversion of RPM/RCF.
- \* External cold-rolled steel with powder coating steel, stainless steel centrifugal chamber.
- \* Procedures of adjustable speed from grad 0 to 9 and 40 kinds of self-defining models.
- \* Functions: Electronic lock lid, imbalance detection, over-speed protection, inching function, short-spin function.

### Technical Parameters:

|                        |  |
|------------------------|--|
| Model                  | BKC-TH16II   |
| Max. Capacity          | 4*100ml  |
| Max. Speed             | 16600rpm   |
| Max. RCF               | 19200×g  |
| Speed Precision        | ±30rpm   |
| Timing Range           | 0~99min  |
| Noise                  | ≤58dB  |
| Power Supply           | AC220±22V 50/60Hz(Standard); AC110V 60Hz(Optional) |
| External Size(W*D*H)mm | 450*350*360  |
| Package Size(W*D*H)mm  | 760*440*530  |
| Net Weight(kg)         | 30   |
| Gross Weight(kg)       | 60   |

### Rotor:

| No.   | Rotor       | Max. Speed(rpm) | Max. RCF(xg) | Max. Capacity | Dimension of Tube(mm) |
|-------|-------------|-----------------|--------------|---------------|-----------------------|
| No.1  | Angle Rotor | 16600           | 19200        | 18*0.5ml      | Φ8*32                 |
| No.2  |             | 16600           | 19200        | 12*2.0/1.5ml  | Φ10*42                |
| No.3  |             | 13000           | 14740        | 48*0.5ml      | Φ8*32                 |
| No.4  |             | 13000           | 16060        | 24*2.0/1.5ml  | Φ10*42                |
| No.5  |             | 13000           | 11500        | 10*5ml        | Φ14*54                |
| No.6  |             | 12000           | 14800        | 12*10ml       | Φ16*87                |
| No.7  |             | 12000           | 14800        | 6*50ml(●)     | Φ29*106               |
| No.8  |             | 12000           | 14800        | 6*50ml(▲)     | Φ29*116               |
| No.9  |             | 10000           | 10290        | 12*15ml(▲)    | Φ16*102               |
| No.10 |             | 10000           | 11200        | 4*100ml       | Φ38*119               |
| No.11 | Micro Plate | 4000            | 2300         | 2*2*48 well   | Microplate            |

With mark(●) or no mark is round-bottom tube, with mark(▲) is sharp-bottom tube

## Table Top High Speed Centrifuge

### Application:

The instrument applies to the experiments in fields of biology, medical science, agriculture, which is the first choice for heredity gene, protein nucleic acid PCR experiment.

### Features:

- \* 5-inch high-definition touch screen, easily operated, visual display.
- \* Automatically identify 7 kinds of different rotors, eliminate hidden danger brought by users' maloperation.
- \* 9 ranges for raising speed, 10 ranges for speed reduction, to effectively avoid secondary sedimentation, with better centrifugation effect.
- \* Available to store 15 series of procedure for users to adjust.
- \* Alternating frequency conversion electric machine, high precision of rotary speed control.
- \* Diverse protection setting: overspeed protect, door protect, imbalance protect, to ensure safety of both human and machine.
- \* Free conversion between rotary speed and centrifugal force.
- \* Special air duct ensures that the rotors work at normal temperature.
- \* Air-tight rotor, to effectively avoid aerosol.



### Technical Parameters:

|                        |   |
|------------------------|---|
| Model                  | BKC-TH16D   |
| Max. Speed             | 16500rpm  |
| Max. RCF               | 21380×g   |
| Max. Capacity          | 4*100ml   |
| Motor                  | Ac frequency conversion motor                                   |
| Speed Precision        | ±30rpm  |
| Time Range             | Centrifugal time: 1min~99 min59sec; Continuous centrifuge: Hold |
| Power Supply           | AC220±22V 50/60Hz(Standard); AC110V 60Hz(Optional)              |
| Noise                  | < 60dB(A)   |
| External Size(W*D*H)mm | 350*495*350   |
| Package Size(W*D*H)mm  | 710*450*520   |
| Net Weight(kg)         | 30  |
| Gross Weight(kg)       | 48  |

### Rotor:

| No.   | Rotor       | Max. Speed(rpm) | Max. RCF(xg) | Max. Capacity | Dimension of Tube(mm) |
|-------|-------------|-----------------|--------------|---------------|-----------------------|
| No.1  | Angle Rotor | 16500           | 18400        | 12*2.2/1.5ml  | φ10*42                |
| No.2  |             | 13000           | 19080        | 48*0.5ml      | φ8*32                 |
| No.3  |             | 15000           | 21380        | 24*2.2/1.5ml  | φ10*42                |
| No.4  |             | 13000           | 19270        | 32*2.2/1.5ml  | φ10*42                |
| No.5  |             | 12000           | 10100        | 12*5ml        | φ13*53                |
| No.6  |             | 12500           | 16060        | 12*10ml       | φ16*83                |
| No.7  |             | 12000           | 15130        | 6*50ml(●)     | φ29*106               |
| No.8  |             | 12000           | 15130        | 6*50ml(▲)     | φ29*116               |
| No.9  |             | 12000           | 15370        | 8*15ml(▲)     | φ17*121               |
| No.10 |             | 10000           | 10620        | 4*100ml       | φ38*119               |
| No.11 | Microplate  | 4000            | 2000         | 2*2*48well    | Microplate            |
| No.11 | Angle Rotor | 13000           | 16200        | 6*8*0.2ml PCR | /                     |

With mark(●) or no mark is round-bottom tube, with mark(▲) is sharp-bottom tube