

**Class B series**

As a type of high pressure sterilizer, it takes steam as its sterilization medium which is fast, safe and economic. They are common used in medical health care institution or R&D institution to make the sterilization for wrapped or unwrapped instrument, fabric, utensils, culture medium, unsealed liquid, etc.



**Features:**


**\* Brand-new operation interface**

The LCD touch screen can display temperature, pressure, time, operating status, error and alarm information, etc.

There are different color changes in each stage of sterilization.

It is convenient for users to observe the sterilizer running status.

More importantly, the fault alarm not only displays the fault code, but also automatically displays the reason analysis and solution.



**\* Multiple safety protection devices**


Automatic over-temperature protection device, multiple control and protection of evaporator, door safety interlock protection, double over-pressure protection device, etc.

**\* Mobile temperature sensor**

The mobile temperature probe can directly detect the internal temperature of the liquid to ensure the sterilization effect of the liquid.

**\* Automatic door structure**

Sterilizer adopts automatic door structure, which is fast and convenient to operate, effectively protects human body and prevents scalding.



**\* Vacuuming system**

High efficiency vacuum extraction system, low working noise, over -90KPa extreme vacuum, fast extraction speed, good dryness, more complete sterilization

**\* A variety of programs**

There are exposed procedures, packaging procedures, rubber procedures, dressing procedures, liquid procedures, liquid customization, solid customization, medium sterilization procedures, B&D testing, vacuum testing and media dissolution procedures.



**\* Other features**

A. Heating, sterilizing, exhausting and drying totally automatic.

B. Chamber is heated by film heater, saving energy and time.

C. 0.22µm high efficiency air filter, to avoid re-contamination of sterilized materials with filtration efficiency over 99.5%.

D. Water filter in tank and chamber are quick to disassemble and easy for cleaning.

E. Built-in stainless steel water tank, inner cycle of steam and water.

F. Standard built-in printer.

G. Standard USB port.

**Technical Parameters:**

Model	BKM-Z45B	BKM-Z60B	BKM-Z80B
Capacity	45L	60L	80L
Chamber Size(mm)	φ316*621	φ386*520	φ386*692
Design Pressure	-0.1/0.3MPa		
Sterilization Temperature	105°C~134°C		
Chamber Material	SUS304		
Ambient Temp.	5°C~40°C		
Consumption	5.8KW	6.2KW	
Power Supply	AC220V, 50Hz(Standard); AC110/220V, 60Hz(Optional); Wiring Method: Air switch		
External Size(W*D*H)mm	610*1020*610	805*940*700	805*1140*700
Package Size(W*D*H)mm	750*1200*880	960*1130*940	960*1330*940
Gross Weight(kg)	165	215	230

Note: It is applicable to the altitude below 3000 meters, and the parts need to be changed when the altitude is over 2000 meters.