Portable Refrigerator



BJPX-L45



BJPX-L110



GPS Temperature and Humidity Data Logger



Smart Temperature & Humidty Data Logger



Bluetooth Printer

Introduction:

Portable refrigerator is a mobile, insulated storage and transport container. The box body features a high-density thermal insulation layer and relies on ice packs to maintain the internal temperature. The product has a compact size and light weight, and is equipped with a handle or wheels for easy short-distance transfer and carrying.

Features:

* PP plastic outer casing: robust, durable, and highly impact-resistant.
* CFC-free polyurethane foam insulation: eco-friendly and odorless.
* Dedicated thickened ice packs for long-lasting temperature control.
* Easy to use; ideal for power-free transport scenarios.
* Professional sealing gasket for superior thermal insulation and cold retention.
* Wheeled design with dual side handles for easy transport.
* Zero electrical hazards for high safety.

Technical Parameters:

Model	BJPX-L45	BJPX-L110
Capacity	45L	110L
Internal & External Materials	PP+PE	
Insulation Material	PU	
Temp. Resolution	0.1℃	
Manufacturing Process	Blow molding + injection molding, burr-free surface	
Cooling Source Material	Sodium polyacrylate	
Cooling Retention Time	Maintains an internal temperature of 2~8°C for 24 hours at an ambient temperature up to 25°C	
Configuration	Refrigerator*1, sample isolation box*1, ice pack(1600ml)*4, digital thermometer*1	Refrigerator*1, sample isolation box*1, ice pack(1600ml)*11, digital thermometer*1
Optional Accessories	GPS temperature and humidity data logger, bluetooth printer, smart temperature & humidty data logger	
Internal Size(W*D*H)	445*290*340mm	795*415*405mm
External Size(W*D*H)	578*380*410mm	940*550*495mm
Package Size(W*D*H)	630*445*495mm	970*600*580mm
Net Weight	7.8kg	18kg
Gross Weight	9.5kg	22kg

BIOBASE
E-mail: export@biobase.com
www.biobase.cc / www.biobase.com