

Flake Ice Maker



Technical Parameters

Model	FIM20	FIM30	FIM40	FIM50	FIM60	FIM70	FIM85
Ice Making Capacity(kg/24h)	20	30	40	50	60	70	85
Max. Ice Storage Capacity	10kg	15kg			25kg		
Ice Shape	Small particle of irregular snow ice						
Input Current	280W	300W	360W	380W	420W	460W	480W
Way of Condensation	Air cooling						
Ambient Temperature	10~35℃						
Water Temperature	2~15℃						
Tank Shell	Stainless steel						
Compressor	Donper		Panasonic Wanbao				
Refrigerant	R290, 30g		R290, 35g		R290, 42g		
Standard Accessory	Water inlet pipe*1, drainage pipe*1, ice spoon*1						
Optional Accessory	Filter						
Power Supply	AC 220V,50/60Hz(Standard); 110V, 60Hz(Optional)						
External Size(W*D*H)	330*470*605mm		400*543*700mm		400*510*845mm		
Package Size(W*D*H)	460*595*740mm		520*665*845mm		520*630*995mm		
Net Weight	26kg		36kg		42kg		
Gross Weight	42kg		55kg		62kg		
Applicable Area	Various types of experiments, hospitals, schools, laboratories,medical, chemical applications, supermarkets, hotels and other seafood products stores etc.						

Flake Ice Maker



Technical Parameters

Model	FIM100	FIM120	FIM150	FIM200	FIM250
Ice Making Capacity(kg/24h)	100	120	150	200	250
Max. Ice Storage Capacity	40kg			60kg	
Ice Shape	Small particle of irregular snow ice				
Input Current	520W	550W	680W	1040W	1100W
Way of Condensation	Air cooling				
Ambient Temperature	10~35℃				
Water Temperature	2~15℃				
Tank Shell	Stainless steel				
Compressor	Panasonic Wanbao	Donper		Panasonic Wanbao	
Refrigerant	R290, 55g	R290, 62g	R290, 65g	R290, 140g	
Standard Accessory	Water inlet pipe*1, drainage pipe*1, ice spoon*1				
Optional Accessory	Filter				
Power Supply	AC 220V,50/60Hz(Standard); 110V, 60Hz(Optional)				
External Size(W*D*H)	500*611*950mm			680*740*1100mm	
Package Size(W*D*H)	630*730*1110mm			730*800*1270mm	
Net Weight	58kg	60kg		80kg	
Gross Weight	82kg			105kg	
Applicable Area	Various types of experiments, hospitals, schools, laboratories,medical, chemical applications, supermarkets, hotels and other seafood products stores etc.				