

BP-PB/L Series Electronic Precision Balance

- Features:**
- * Wide-viewing-angle high-definition LCD display.
 - * Unit conversion(g/ct/oz).
 - * Min weighing set.
 - * Overload alarm/level indicator.
 - * Features low power consumption and adapts to various lighting conditions.



Technical Parameters:

Model	BP103PB	BP203PB	BP303PB	BP103PL
Capacity	110g	210g	310g	110g/610g
Resolution	1mg			1mg/10mg
Min Weighing	4mg			1d~4d
Repeat Ability	±2mg			±2d
Liner	±3mg			±3d
Stable Time	≤3s			
Pan Size	Φ90mm			Φ110mm
Draft Shield Size(W*D*H)	240*195*265mm			
Appearance Size(W*D*H)	270*200*270mm			
Optional	Dual display, interface, printer, dust cover			
Calibration	External calibration			
Power Supply	AC110~220V±10%, 50/60Hz			
Cal.Weight	100g	200g		
Interface	RS232C(Standard)			
Packing Size(W*D*H)	300*380*390mm			
Gross.Weight	4kg			

BP-N Series Electronic Precision Balance

- Functions:**
- * Electromagnetic force balance sensor.
 - * Cast aluminum housing with large-space windshield.
 - * Wide-view LCD high-definition display.
 - * Full-range tare function.
 - * Counting function.
 - * Percentage weighing.
 - * Unit conversion (g/mg/ct/oz, etc.).
 - * Adjustable sensitivity / response speed.
 - * Overload alarm / fault alarm / level indicator.



Technical Parameters:

Model	BP203N	BP303N	BP403N	BP503N	BP603N
Capacity	200g	300g	400g	500g	600g
Resolution	1mg				
Min Weighing	4mg				
Repeat Ability	±2mg				
Operation Temp	5~25℃				
Liner	±3mg				
Stable Time	≤3s				
Pan Size	Φ80mm				
Draft Shield Size(W*D*H)	240*190*265mm				
Optional	RS232C, brinter, underhook weighing				
Calibration	Auto timed internal calibration / one-key calibration.				
Power Supply	AC220V±10%, 50Hz; 110V±10%, 60Hz				
Cal.Weight	100g			200g	
Packing Size(W*D*H)	490*360*530mm				
Gross Weight	10kg				