

Laboratory Refrigerator(Economic Type)



Technical Parameters

Model	BPR-5V46F		BPR-5V150F	BPR-5V320F	BPR-5V400F
Capacity	46L		150L	320L	400L
Temp. Range	2~8℃				
Temp. Accuracy	1℃				
Temp. Uniformity	≤2℃				
Temp. Stability	≤3℃				
Control System	Microprocessor control				
Display	LED				
Alarm	High and low temperature alarm, thermostat fault alarm, door switch alarm				
Refrigeration Type	Air-cooling				
Refrigerant	R600a/25g		R600a/31g	R600a/34g	R600a/38g
Compressor	International famous brand compressor /1				
Condenser & Evaporator	Bundy tube, side plate type; aluminum plate, roll-bond evaporator		Bundy tube, side plate type; aluminum tube, plate and tube evaporator		Bundy tube, inside style; aluminum plate, plate and tube evaporator
Defrost	Automatic defrost				
Construction	Polyurethane cyclopentane foam				
Material	Internal Material	HIPS			
	External Material	Precoated steel plate			
Door	1/Cyclopentane monolithic foam door				
Consumption	85W		130W	180W	180W
Power Supply	AC 220V, 50Hz(Standard); 220V, 60Hz, 110V, 60Hz(Optional, external transformer)				
Casters	No				
Adjustable Shelf	1		2	5	6
Standard Accessory	Test hole, shelf				
Internal Size (W*D*H)	400*295*426mm		490*480*712mm	490*480*1408mm	490*480*1778mm
External Size (W*D*H)	480*460*585mm		600*607*870mm	600*607*1560mm	600*607*1930mm
Package Size (W*D*H)	520*520*710mm		640*660*1040mm	640*660*1770mm	640*660*2140mm
Net Weight	18kg		32kg	52kg	63kg
Gross Weight	26kg		44.5kg	66.5kg	81kg