

Tissue Grinding Machine



Introduction:

Tissue Grinding Machine can extract and purify original DNA, RNA, and proteins from any source, including soil, plant and animal tissues/organs, bacteria, yeast, fungi, spores, paleontological specimens, etc. It completes the grinding, crushing, mixing, and cell wall disruption of samples in a very short time.



Features:

- * In standard mode, both BHY1 and BHY2 can process up to 24 samples in as little as 1 minute.
- * The grinding process is fully enclosed, with samples moving independently to avoid cross-contamination.
- * BHY2 has been upgraded to a dual-slide vertical oscillation mechanism, providing more thorough grinding, better stability, and a longer lifespan. BHY1 features a wear-resistant graphite bush structure.
- * Supports placing centrifuge tubes directly into the adaptor, supports pre-freezing of centrifuge tubes.
- * Adopt for quiet operation to reduce interference with the surrounding environment.

Applicable Samples:

- * Animal tissues: brain, heart, lungs, stomach, liver, thymus, kidneys, intestines, lymph nodes, muscles, bones, hair, etc.
- * Volatile samples: coal, oil shale, wax products, etc.
- * Plant tissues: roots, stems, leaves, flowers, fruits, seeds, etc.
- * Microorganisms: yeast, E. coli, etc.
- * Food and pharmaceuticals: various foods, tablets, etc.
- * Plastics, polymers: PE, PS, textiles, resins, etc.
- * Environmental samples: soil, sediment, sludge, feces, etc.

Adaptor:

Model	Standard	Optional				
BHY1	 24*2ml	 32*2ml	 16*5ml			
BHY2	 24*2ml	 96*2ml	 48*2ml	 32*2ml	 16*5ml	 8*10ml
		 2*50ml	 2*25ml	 2*15ml		
		Not suitable for low temperature grinding: 96*2ml/48*2ml				

Technical Parameters:

Model	BHY1	BHY2
Display	5-inch OLED touch screen	7-inch OLED touch screen
Oscillation Mode	Up and down vertical oscillation	
Grinding Speed	500~2300rpm	
Grinding Way	Dry grinding/wet grinding/low temperature grinding	
Grinding Time	Each segment 0~120s, can be set in multiple segments	
Programming	Multi-stage operation setup is available, automatically records the parameters of the last operation	
Safety Lock	Mechanical butterfly safety lock + door-controlled electronic operation limit	
Adaptor	Aluminum alloy material	Aluminum alloy material
	Standard: 24*2ml Optional(Can customize): 32*2ml/16*5ml	Standard: 24*2ml Optional(Can customize): 96*2ml/48*2ml/ 32*2ml/16*5ml/8*10ml/2*15ml/2*25ml/2*50ml Not suitable for low temperature grinding: 96*2ml/48*2ml
Grinding Ball	Standard stainless steel grinding ball: φ3mm*800 and φ5mm*200	Standard stainless steel grinding ball: φ3mm*800 and φ5mm*200
Consumption	120W	180W
Power Supply	AC 110~220V, 50/60Hz	
External Size(W*D*H)	265*405*475mm	265*405*520mm
Package Size(W*D*H)	375*510*640mm	375*530*670mm
Net Weight	28.5kg	27kg
Gross Weight	41kg	

Note: Low temperature grinding means that the some adapter can be placed in a low temperature refrigerator or liquid nitrogen container to take out and then use, rather than the instrument with its own freezing function