


Microplate Centrifuge



Rotor:
Capacity: 2*96 well PCR plate
Speed: 2800 rpm;
RCF: 755×g

Introduction:

The microplate centrifuge BKC-TL3MP is a transient centrifuge specially designed for microplate centrifuge, for easy separation from the bottom wall fluid. It is suitable for skirted, non-skirted and various standard PCR microplates.

Features:

- * The whole machine adopts steel structure, safe and reliable, durable.
- * Aluminum alloy rotor, high strength, no pollution, can be sterilized at high temperature.
- * Two operating modes, touch operation and timing operation, make the experiment more convenient and efficient.
- * Embedded microprocessor control, DC brushless motor drive, maintenance-free, smooth operation.
- * Instant acceleration to 2800rpm, electronic brake, it takes only 15s to stop.
- * Push-button programming design, LCD display, all parameters real-time displayed.
- * Optional automatic rotor recognition.

Technical Parameters:

Model	BKC-TL3MP
Max. Capacity	2*96 well
Max. Speed	2800rpm
Max. RCF	755×g
Timing Range	1s~99s (short-spin)
Speed Precision	±15rpm
Noise	≤60dB
Consumption	50W
Power Supply	AC100~260V, 50/60Hz
External Size(L*W*H)	200*250*230mm
Package Size(L*W*H)	290*290*270mm
Net Weight	5.5kg
Gross Weight	6kg

Rotor:

NO.	Rotors Type	Capacity	Max. Speed	Max.RCF
1	Microplate Rotor	2*96 well PCR plate/2*12*8*0.2ml PCR strips/2*96*0.2ml PCR tube	2800rpm	755×g

Microplate Centrifuge



Rotor:
Capacity: 2*2*96well
Speed: 4000 rpm RCF: 2361 xg

Introduction:

The microplate centrifuge BKC-TL4MP is often used in PCR experiments to quickly remove droplets from the lower wall and significantly improve the experimental results. It is suitable for skirted, non-skirted and various standard PCR microplates, suitable for biochemical, Molecular biology, ELISA and isolation of general experimental samples, etc.

Features:

- * The 5-inch touch LCD screen supports language customization, and the operation interface is intuitive and simple.
- * It adopts electromechanical integration door lock, which is easy to use, safe and reliable.
- * Silicone integral sealing ring is used to avoid aerosol overflow and ensure the safety of staff.
- * With self-test, stall, overspeed, unbalance and other detection and alarm functions.
- * Excellent shock absorption device to ensure the smoothness of the motor.
- * Multiple groups of user-defined programs can be stored.
- * Optional automatic rotor recognition.

Technical Parameters:

Model	BKC-TL4MP
Max. Capacity	2*2*96 well microplate/ELISA plate, 2*96 deep-well plate
Max. Speed	4000rpm
Max. RCF	2361×g
Timing Range	1s~99h59min/continuous/short-spin
Speed Precision	±20rpm
Noise	≤65dB (A)
Consumption	500W
Power Supply	AC220V, 50/60Hz (Standard); 110V, 50/60Hz (Optional)
External Size(L*W*H)	440*580*370mm
Package Size(L*W*H)	536*676*481mm
Net Weight	41kg
Gross Weight	49kg

Rotor:

NO.	Rotors Type	Capacity	Max Speed	Max RCF
5M00045	Microplate Rotor	2*2*96 well	4000rpm	2361×g