

High Speed Dispenser



Introduction:

It rapidly breaks down the material particles, achieving uniform dispersion, dissolution and mixing of powder and liquid materials. It is widely used in the pharmaceutical industry, food industry and other fields.

Features:

- * LED digital display for clear, intuitive speed readout; speed range: 100~8000 rpm.
- * AC motor with stepless speed regulation, featuring high torque, high output power, and stable operation.
- * Stainless steel double-layer barrel, capable of introducing cooling liquid to evenly disperse the sample at a constant temperature, and easy to clean.
- * Standard with an adjustable vessel holder for secure fixation, ensuring worry-free operation.

Technical Parameters:

Model	BJPX-LFS
Speed Range	100~8000rpm
Processing Volume	0.5~5kg
Barrel Capacity	1.5L
Maximum Viscosity	10000mPa·s
Lifting Stroke	250mm
Lifting Type	Manual chain lifting with square steel tube structure
Motor	Brushed AC motor
Dispersion Disc	Φ50mm, Φ60mm
Sand Grinding Disc	Φ60mm
Consumption	400W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 50/60Hz(Optional, external transformer)
Packing Size(W*D*H)	480*480*860mm
Gross Weight	37kg

BIOBASE

E-mail: export@biobase.com

www.biobase.cc / www.biobase.com