

## **Horizontal Cylindrical Pressure Autoclave**



## Features:

\* Brand New Operation Interface

The LCD touch screen can display temperature, time, operating status and fault alarm in real time, making the sterilization information more intuitive and clear and it is convenient for users to observe the operating status of the equipment.

\* Drying Function

With auxiliary drying function, it is used to dry sterilized items.

\* Protection Device

Equipped with over-temperature and over-pressure automatic protection devices.

\* Steam Generato

The equipment has a built-in high-speed steam generator, which saves time and effort without external steam source.

\* Automatic Operation of The Program

The equipment is externally connected to the water source and there is no need for manual water replenishment. After the customer selects the program, the equipment can complete the entire process from water injection to drying without human intervention. After the program is completed, the sound prompts that the sterilization is complete.

\* Programs: Wrapped, Unwrapped, Dressing, Rubber, Drying, DIY solid

## Technical Parameters:

Model	BKQ-H150	BKQ-H200	BKQ-H300	BKQ-H400
Capacity	150L	200L	300L	400L
Designed Pressure	0.28MPa			
Built-in Steam Generator	Yes			
Rated Working Pressure	0.12MPa/0.23MPa			
Rated Operating Temperature	121°C/134°C			
Ambient Temp.	5-40℃			
Adjustable Drying Temperature Range	115~134℃			
Temp. Control Precision	0.1℃			
Sterilization Timing Adjustable Range	0-99min			
Adjustable Drying Timing Range	0-99min			
Vacuum System	No Shiobasa aam			
Chamber Material	304 stainless steel			
Chamber Size (Φ*L)	Ф500*820mm	Ф500*1050mm	Ф650*935mm	Ф650*1235mm
Power Supply	Three-phase AC380V, 50/60Hz; Three-phase AC220V, 50/60Hz; Single-phase AC220V			
	50/60Hz (Note: Be careful when ordering this voltage, the current is close to 75A)			
Rated Power	16KW			
Altitude	<3000m			
Standard Accessories	Net rack*1, Net lid*1			
External Size(W*D*H)	1270*680*1550mm	1500*680*1550mm	1550*815*1750mm	1850*815*1750mr
Package Size(W*D*H)	1500*820*1910mm	1730*820*1910mm	1750*950*2030mm	2000*950*2030mr
Net Weight	230kg	250kg	340kg	385kg
Gross Weight	320kg	355kg	475kg	535kg

09