



Vertical Laminar Flow Cabinet

—Return Air Type




LCD display

Display content: wind speed, time, including the working time of the UV lamp and the working time of the filter.



Two splashproof sockets.



UV Lamp

Emission of 254 nanometers for most efficient decontamination.

ADVANTAGE

- * Air return type structure design: Part of the clean air is recycled to reduce the operator's blowing feeling and prolong the life of the filter.
- * Product safety: the number of colonies is less than or equal to 0.5CFU/30min.
- * Filtration efficiency: For 0.3 μm particles, the filtration efficiency can reach 99.995%.

TECHNICAL PARAMETERS

Model	BBS-V1100-XF	BBS-V1500-XF	BBS-V1800-XF
Airflow Pattern	Vertical laminar flow, return air		
Applicable number of people	1	2	3
External Size(W*D*H)	1100*710*1850mm	1500*710*1850mm	1800*710*1850mm
Instrument Size(W*D*H)	1000*575*625mm	1400*575*625mm	1700*575*625mm
Work Surface Height	750mm		
Max Opening	400mm		
Air Velocity	0.3~0.45m/s		
Airflow Volume	750m³/h		
Noise	≤65dB(A)		
LED Lamp	12W*1	16W*1	16W*1
UV Lamp	20W*1	40W*1	40W*1
Power Supply	220V±10%, 50/60Hz; 110V±10%, 60Hz		
Consumption	700W	750W	900W
HEPA Filter	1 pc		
Gross Weight	190kg	240kg	280kg
Package Size (W*D*H)	1240*1050*1350mm	1640*1050*1350mm	1940*1050*1350mm