



## PP Vertical Laminar Flow Cabinet



### ADVANTAGE

1. Made of PP material, integrally welded
2. Resistant to strong acid, alkali and strong corrosion
3. With memory function in case of power-failure
4. Interlock function: UV Lamp and blower, LED Lamp
5. The work surface is seamlessly welded with PP plate, which is convenient for overall cleaning



**LED Display**  
Airflow velocity, UV exposure time.



**Waterproof Socket**  
Waterproof socket is located in the back panel, for optimum convenience of using small devices inside the cabinet.



**UV Lamp**  
Emission of 253.7 nanometers for most efficient decontamination.



**Footmaster Caster**  
Universal caster with brake and leveling feet

### TECHNICAL PARAMETERS

Model	BKCB-800P	BKCB-1000P	BKCB-1200P	BKCB-1500P
External Size (W*D*H)	800*710*1800mm	1000*710*1800mm	1200*710*1800mm	1500*710*1800mm
Internal Size (W*D*H)	780*540*550mm	980*540*550mm	1180*540*550mm	1480*540*550mm
Work Surface Height	750mm			
Material	Made of Porcelain white PP, resistant to strong acid, alkali and anti-corrosion.			
Side Window	5mm toughened glass, anti-UV			
Front Window	Manual			
Pre-filter	Polyester fiber			
HEPA Filter	99.995% efficiency at 0.3μm			
Airflow Velocity	0.3~0.5m/s			
Noise	≤65dB			
Max Opening	400mm			
UV Lamp	20W*1			
LED Lamp	8W*1			
Illumination	≥350lx			
Caster	Footmaster Caster			
Waterproof Socket	One, total load≤500W			
Consumption	650W	650W	700W	850W
Standard Accessory	UV lamp*1; LED lamp*1; Waterproof socket*1; Base stand			
Power Supply	AC220V, 50/60Hz(Standard); 110V, 50/60Hz(Optional)			
Package Size (W*D*H)	950*950*1300mm	1150*950*1300mm	1350*950*1300mm	1650*950*1300mm
Gross Weight	90kg	110kg	130kg	150kg