



Ducted Fume Hood



ADVANTAGE

1. Adjustable air speed: 9 levels.
2. Microprocessor control system, LED display.
3. Resistant to moderate acid and alkali.
4. With memory function in case of power-failure.
5. Manual front glass window, height adjustable.
6. Built-in PP centrifugal blower; low noise, easy installation.

TECHNICAL PARAMETERS

Model	FH1000(E)	FH1200(E)	FH1500(E)	FH1800(E)	
External Size(W*D*H)	1000*800*2515mm	1200*800*2515mm	1500*800*2515mm	1800*800*2515mm	
Internal Size(W*D*H)	790*600*870mm	990 *600*870mm	1290*600*870mm	1590*600*870mm	
Work Surface Height	900mm				
Max Opening	750mm				
Air Velocity	0.3~0.8m/s				
System Exhaust Volume	570 m ³ /h	710 m ³ /h	930 m ³ /h	1140 m ³ /h	
Noise	≤68dB				
Exhaust Duct	PVC,Standard length; 5 meters,Φ300mm				
Pipe Strap	2 pcs				
LED Lamp	20W *1		40W *1		
Blower	Built-in PP centrifugal blower				
Front Window	Manual, 5mm toughened glass, height adjustable				
Power Supply	220V±10%, 60/50Hz; 110V±10%, 60Hz				
Consumption	400W	400W	500W	500W	
Material	Exterior	1.0mm cold-rolled steel with anti-bacterial powder coating			
	Interior	Compact laminate board with good acid and alkali resistance function			
	Work table	Chemical resistant phenolic resin			
Standard Accessory	PP Water sink, Total load of 2 waterproof sockets: 500w, Base cabinet, Water tap, 5 meters Exhaust duct(φ300mm).				
Optional Accessory	Air supply flow control valve, gas faucet.				
Gross Weight	270kg	305kg	335kg	365kg	
Package	Main Body	1140*940*1900mm	1340*940*1900mm	1640*940*1900mm	1940*940*1900mm
	Base Cabinet	1140*940*1050mm	1340*940*1050mm	1640*940*1050mm	1940*940*1050mm



LED Display
Digital LED display:
Airflow Level



Waterproof Socket



Universal Wheel



Water Remote Control



Water Tap



Water Tap & Water Sink