

Auto ELISA Processor BIOBASE2001

Introduction:

Auto ELISA Processor BIOBASE2001 is a fully automatic detection equipment that integrates sample addition, incubation, shaking, washing, and reading. It is widely used in hospital laboratories, disease prevention and control centers, blood centers, and blood banks, animal and plant inspection and quarantine institutions, scientific research institutions, university laboratories and other places.

Features:

- ① Adopt the principle of pressure type liquid detection
- ② With TIP detection, clot detection function.
- ③ High-precision pipetting
- ④ Position sensing, real-time monitoring of gripper status.
- ⑤ Multi-spacing and multi-strength adjustable grippers can be adapted to grasp and place microplates and plate covers of different sizes.
- ⑥ Dual thread control, can run simultaneously with the sampling arm without interfering with each other.



Sampling Module

Disposable TIP design, high precision, zero carry-over pollution
2 injection channels are independently controlled, and each channel runs independently in Y-Z direction
With liquid level detection, TIP head detection, clot detection and other detection and alarm functions



Smart Gripper Module

Safe, reliable, stable, efficient, fast and accurate gripper
With position sensing system
Real-time monitoring of the grabbing process to prevent falling



Shaking Incubation Module

8 independent temperature-controlled shaking incubation modules
3-level shaking
Temperature range: RT~60°C
Plate cover design to avoid strong light interference



Microplate Washer Module

2 independent microplate washers, 16-channel (32-pin) washer head, 5-way cleaning solution
Injection uniformity CV < 1.5%, residual volume < 1µL/well
Program adjustable, applicable to microplates of different sizes



Microplate Reader Module

Built-in high-precision microplate reader
Single and dual wavelength detection, ten filter positions
Wide absorbance range, high sensitivity, good repeatability and strong stability

Parameters:

Model	BIOBASE2001	
Sample & Reagent Unit	Sample Racks	6*20 push-pull sample rack with detection
	Sampling Channel	2 channels
	Liquid Level Detection	Air pressure level detection, clot detection function
	TIP	1000ul, 3 TIP racks
	Pipetting	10ul~1000ul
Washing Unit	Pipetting Precision	100ul: CV≤1%, Accuracy≤2.5% 1000ul: CV≤0.5%, Accuracy≤1%
	Reagent Position	4 Reagent racks, reagent tanks with detection
	Washer	1 unit
	Washing Head	16-channel (32-pin), double row cleaning, hanging installation, with leakage recovery
	Injection Uniformity	CV < 1.5%
Reading Unit	Washing Residual	<1µl
	Reading Channels	8 independent photometric channels
	Linear Range	0.000-3.000Abs
	Repeatability	CV≤1.0%
	Stability	≤±0.003Abs
Incubation Unit	Optical Filters	4 standard filters (405,450,492,630nm); Total 10 filters positions
	Reading Accuracy	≤±0.02Abs from 0.0 to 1.0 OD, ≤±0.03Abs from 1.0 to 2.0 OD
	Sensitivity	≥0.01mg/L
	Channel Difference	≤0.02Abs
	Incubators	8 shaking incubators
Data Management	Cover Positions	1 (8 covers)
	Heating Method	Dry heating with cover
	Shaking Function	Horizontal circular oscillation, 1-3 levels adjustable, amplitude 2.5mm
	Temperature Range	RT to 60 °C
	Temperature Uniformity	0.5°C
Other Function	Temperature Fluctuation	±0.5°C
	Software	Above Windows 7 system
	LIS System	Bi-direction, support HL7 protocol
	Results	Absorbance and results reviewable by software
	Printer	External optional
Working Condition	Built-in Scanner	Optional
	Biosafety Protection	Optional (Negative pressure working zone, HEPA filter)
	Disinfection	UV lamp
	Lighting	LED
	IAP Function	Firmware can be upgraded online at any time
Size & Weight	Power Supply	AC220V±10%,50/60Hz(Standard); 110V±10%,60Hz(Optional)
	Temperature	10~40°C
	Humidity	30~80%
	External Size (W*D*H)	1275*750*1650mm
	Net Weight	330kg
Size & Weight	Package Size(W*D*H)	Machine: 1445mm*1130mm*920mm Base Stand: 1445mm*1005mm*920mm Accessories: 1065mm*510mm*895mm
	Gross Weight	Machine: 220kg; Base stand: 125kg; Accessories: 30kg