

## **Automatic Titrator**



## Features:

- \* 10 inch color capacitive screen, modular operating system, GUI navigation icon design, convenient for experimenters to operate.
- \* The instrument is waterproof as a whole, and the connection of the data line is waterproofed to prevent liquid penetration and deposition.
- \* Multi-channel modular combination, can combine multiple feeding units; Support multiple feeding units work at the same time, free combination, no need to install disassembly parts, modules can be simple side by side to build instrument system.
- \* Built-in burette, burette is built into the instrument, the burette can be observed externally through a window.
- \* It Can carry out multiple self-test function, pH electrode calibration function, burette calibration function.
- \* Export detailed and tabular results in PDF and Excel formats and support wireless printing.

## **Technical Parameters:**

Model		BK-PT10
PH	Range	-20.000pH~+20.000pH
	Resolution	0.001
	Accuracy	±0.003
ORP	Range	-2000.0mV~+2000.0mV
	Resolution	0.1
	Accuracy	±0.03%
Temperature	Range	-5~120℃
	Resolution	0.1℃
	Accuracy	±0.1℃
Burette	Specification	10ml (Standard); 5ml/25ml (Optional)
	Resolution	1/48000
	Supplementary Speed	16s (when burette is full scale)
Stirring Method		Magnetic stirring
Interface Type		mV/pH measuring electrode interface, reference electrode interface,
		temperature electrode interface, USB port, power port
Package Size(W*D*H)		545*457*460mm
Net Weight		13kg
Gross Weight		15kg