

Blood Collection Monitor



Features:

- * 7.0 inch HD IPS touch screen, Chinese and English guided graphic operation interface, easy to complete blood collection.
- * The screen also displays the blood collection weight and volume.
- * Microcomputer program control, automatic clamping line, accurate collection of blood volume.
- * There is an alarm when the flow rate is too high and too low, and the flow rate range can be set.
- * Real-time display of blood collection progress and completion.
- * According to the blood collection volume requirements, the corresponding collection preset value can be quickly selected.
- * Automatically record and store up to 999 pieces of collected data, which can be exported and stored in a computer to achieve data information management.
- * Optional scanning gun.

Technical Parameters:

| Model | BCM-12C |
|--------------------------------------|---|
| Measuring Range | 20~1200ml |
| Preset 4 Gears Collection Presets | 100ml |
| | 200ml |
| | 300ml |
| | 400ml |
| Display | 7.0-inch HD IPS touch screen |
| Resolution | 1ml |
| Liquid Proportion | 1.05g/ml |
| Collection Speed | 0.5~3ml/s |
| Static Error | ±1% |
| Swing Angle | 13±2° |
| Swing Frequency | 30~32r/min |
| Alarm | Buzzer alarm sound |
| Obstruct Pipeline | Outer diameter $\phi 3 \sim \phi 6$ mm, wall thickness: 0.5mm |
| Obstruct Resistance | ≥14N |
| Ambient Temperature | 0~40°C, relative humidity less than 85% |
| Consumption | 50W |
| Power Supply | AC110/220V±10%, 50/60Hz |
| External Size(W*D*H) | 380*220*150mm |
| Net Weight | 5.2kg |
| Packing Size(W*D*H) | 470*300*250mm |
| Gross Weight | 7kg |