

Bottle-Top Dispenser



Features:

- * Excellent chemical resistance.
- * Fully autoclavable at 121°C.
- * Adjustable control knob makes setting the volume easy.
- * Made of PTFE, FEP, BSG, PP.
- * Vapor pressure Max. 500mbar, viscosity max. 500mm²/s, temperature max. 40°C, density max. 2.2g/cm³.

Technical Parameters:

Volume Range	Subdivision	Accuracy	Precision	Package	Gross Weight(kg)	Package Size(mm)
1ml	/	±2.00%, 20µl	1.00%, 10µl	20pcs/carton	14	595*430*275mm
0.5-5ml	0.1ml	±0.50%, 25µl	0.10%, 5µl	20pcs/carton	14	595*430*275mm
1-10ml	0.2ml	±0.50%, 50µl	0.10%, 10µl	20pcs/carton	14	595*430*275mm
2.5-25ml	0.5ml	±0.50%, 125µl	0.10%, 25µl	20pcs/carton	14	595*430*275mm
5-50ml	1.0ml	±0.50%, 250µl	0.10%, 50µl	20pcs/carton	14	595*430*275mm

Accessories:

Accessory Code	Description	Accessory Code	Description
30013110	Adapt 45/40mm	30013150	Adapt 32/28mm
30013120	Adapt 45/32mm	30013160	Bottle(Brown, 1L)
30013130	Adapt 45/38mm	30013170	Filling tube(m)
30013140	Adapt 32/25mm	30013180	Discharge tube(m)