

## Constant Temperature Water Tank



### Features:

- \* Precise Timing
  - Timer can accurately control the heating time
  - Timing range: 0~9999 minutes/hours
  - Timing error: <1%
- \* LCD Display
  - Real-time temperature display countdown display
- \* Inside Design
  - Powder-coated steel outer shell, durable
  - The fully rounded inner cavity is easy to clean and disinfect
- \* Temperature Difference Calibration
  - Equipped with temperature deviation calibration function
- \* Temperature Control
  - PID microprocessor control
  - Standard over-temperature alarm function

### Technical Parameters:

Model	WT-26	WT-420	WT-100
Temp. Range	R.T.+5~100°C(Normal atmosphere)		
Temp. Fluctuation	±5°C		≤±2°C
Temp. Accuracy	0.1°C		
Capacity	30L	13.6L	100L
Consumption	1500W		
Power Supply	220VAC±10%, 110VAC±10%; 50/60Hz		
Lid Size	Φ37, Φ58, Φ79, Φ100, Φ120		
Internal Size(L*W*D)	500*300*200mm	420*180*204mm	1330*450*170mm
External Size(L*W*D)	641*340*288mm	597*258*270mm	1501*523*288mm
Package Size(L*W*D)	671*370*323mm	650*310*330mm	1550*575*330mm
Net Weight	12kg	8.8kg	40kg
Gross Weight	15kg	11.5kg	45kg