

Constant Temperature Drying Oven



Features:

- * LCD liquid crystal temperature display, with temperature deviation calibration function.
- * Over-temperature alarm and automatic fault detection alarm function.
- * Precisely control the heating time, the timing error is $\leq 1\%$.
- * The four corners of the inner cavity are designed with a semi-circular arc structure.
- * The heating device is placed at the bottom, and a new bottom wind plate structure is adopted to facilitate the cleaning of the cavity.

Technical Parameters:

Model	BJPX-HDO43	BJPX-HDO55	BJPX-HDO72	BJPX-HDO138	BJPX-HDO270
Capacity	43L	55L	72L	138L	270L
Heating Method	Bottom heating, natural convection				
Temp. Range	RT+10°C-250°C				
Display	LCD display				
Temp. Uniformity	$\leq \text{Max temp.} \pm 3\%$				
Temp. Precision	0.1°C				
Inner Size(mm)	350*350*350	370*370*459	400*390*450	500*500*550	600*600*750
External Size(mm)	579*474*565	596*500*666	614*525*659	724*625*759	824*763*954
Shelves NO.	2	2	2	3	3
Power Supply	Standard: 220V 50/60Hz; optional: 110V 50/60Hz				
Packing Size(mm)	640*505*595	656*530*696	674*555*689	784*655*789	884*793*984
Gross Weight(kg)	35	40	50	70	90