

## Electric Heating Thermostat Water Tank



### Features:

- \* Precise Timing  
Timer can accurately control the heating time  
Timing range: 0~9999 minutes/hours  
Timing error: <1%
- \* LCD Display  
Real-time temperature display countdown display
- \* Inside Design  
High-quality cold-rolled steel plate outer shell, the surface is sprayed with environmental protection spray processing, good corrosion resistance.  
The work area is made of S.S. plate.
- \* Temperature Difference Calibration  
Equipped with temperature deviation calibration function
- \* Temperature Control  
PID microprocessor control  
Standard over-temperature alarm function

### Technical Parameters:

Model	WB-8D
Temp. Control	PID digital temperature control
Temp. Range	R.T.+5~100°C(Normal atmosphere)
Temp. Fluctuation	≤±0.5°C
Temp. Accuracy	0.3°C
Temp. Resolution	0.1°C
Timing Range	0~9999 minutes/hours or continuous duty
Heating Mode	S.S. tube calorifier
Capacity	3.9L*3
Consumption	750W
Power Supply	220VAC±10%, 110VAC±10%; 50/60Hz
Work Zoom Size	176*150*150mm
External Size(L*W*D)	533x311x260
Package Size(L*W*D)	573x345x300mm
Net Weight	10kg
Gross Weight	13kg