

## **Fully Automatic High Frequency Heat Sealer**





**BK-HSI** 

**BK-HSII** 

## Feature:

- \* Microcontroller control, instrument control programmed, instrument automatically adjusts voltage.
- \* Heat sealing without hemolysis, using imported components to ensure instrument reliability.
- \* The machine feet have suction cups, suitable for use in blood collection vehicles.
- \* Automatic heat sealing tube, firmly sealed, easy to separate at the heat sealing point.
- \* Splash protection: transparent splash protection film to prevent blood from splashing into the operator's eyes during hot sealing, ensuring the safety of operators.
- \* Convenient cleaning: The white safety cover allows for easy disassembly and cleaning without the need for specialized tools.
- \* Heat sealing voltage: automatic voltage regulation.

## **Technical Parameters:**

Model	BK-HSI	BK-HSII
Material	aluminium alloy	stainless steel
Output Voltage	automatic voltage regulation	
Sealing Type	automatic heat sealing	
Sealing Time	0.1-9.9 seconds	
Tube Size	plastic pipe with an outer diameter of 4mm and a wall thickness of ≤ 1mm	
Power Supply	AC220V, 50Hz	
External Size(L*W*H)(mm)	300*200*160mm	300*180*150mm
Packing Size(L*W*H)(mm)	470*320*260mm	
Net Weight(kg)	8kg	7kg
Gross Weight(kg)	9kg	8kg