



## Fume Hood



**LED Display**  
Digital LED Display:  
Airflow Level



**Footmaster Caster**  
Universal Caster with  
Brake and Leveling Feet



**Base Stand**  
Optional



**Waterproof Socket**

## ADVANTAGE

1. The cabinet is designed with a vertical surface, the operation perspective is wide and more humanized.
2. Made of high quality cold rolled steel plate material, surface electrostatic spraying, with good finish.
3. The platform panel of the operation area of the fume hood is made of solid physical and chemical plate, which is resistant to acid and alkali corrosion and can be disassembled for easy cleaning (integral type).
4. The front window adopts 5mm thick tempered glass to better protect the safety of personnel and experiments.
5. Counterweight manual front window, height adjustable.
6. The base bracket and fuma castor integrated design, safely moved through the casters, also well fixed and levelled.
7. Equipped with PP centrifugal fan, large air volume, low noise, long service life, easy installation.
8. The fan can be stepless speed regulation, the function button is push-button switch, stable performance.
9. The side of the cabinet body is equipped with lifting handles to facilitate carrying.

## TECHNICAL PARAMETERS

Model	BK-FH700	
Number of Users	Single	
Rated Power	95W (Not including socket load power, load power cannot exceed 500W)	
Exhaust Volume	1225 m <sup>3</sup> /h	
Air Velocity	0.3m/s~0.8 m/s	
Noise	≤65dB (A)	
LED Lamp	4W	
Max Opening	410mm(Integral Type)	
Tabletop Height	810mm(Integral Type)	
Standard Accessory	LED Lamp, National standard three core splash proof socket,	
Optional Accessory	Base Stand, Bench physical and chemical board	
Net Weight	Desktop Type	60kg
	Integral Type	80kg
Gross Weight	Desktop Type	78kg
	Integral Type	100kg
External Size (W*D*H)	Desktop Type	700*650*1050mm
	Integral Type	700*650*1850mm
Internal Size(W*D*H)	580*510*687mm	
Package Size (W*D*H)	Desktop Type	1010*850*1250mm
	Integral Type	1010*850*1250mm