

# Laboratory Refrigerator



## Technical Parameters

<b>Model</b>	BPR-5V68F
<b>Type (shelf/drawer)</b>	2 pcs shelves
<b>Material</b>	Plastic-coated steel wire
<b>Refrigeration Mode</b>	Air-cooled
<b>Defrosting Mode</b>	Frost-free
<b>Refrigerant/g</b>	R600a, CFC free/21g
<b>Noise</b>	55dB(A)
<b>Ambient Temp.</b>	10~32°C
<b>Temp. Range</b>	5±3°C
<b>Temp. Accuracy</b>	0.1°C
<b>Evaporator</b>	Plate and tube type; copper tube and aluminum fin
<b>Condenser</b>	Bundy tube
<b>Sensor</b>	NTC
<b>Thermostat</b>	Electronic thermostat
<b>Door</b>	Foamed cyclopentane
<b>Display</b>	LCD
<b>Interface</b>	USB
<b>Power Supply</b>	110~220V/50~60Hz
<b>Power</b>	85W
<b>Current</b>	0.7A
<b>Internal Material</b>	Spray steel plate
<b>External Material</b>	Spray steel plate
<b>Lagging</b>	Foamed polyurethane cyclopentane
<b>Volume</b>	68L
<b>Standard Accessories</b>	High and low temperature alarm, Power fault alarm, Thermostat fault alarm, Door open alarm, LED lamp, USB port
<b>Optional Accessories</b>	Printer, 485 port
<b>Net Weight</b>	38kg
<b>Gross Weight</b>	49kg
<b>Internal Size(W*D*H)</b>	415×405×455mm
<b>External Size(W*D*H)</b>	495×548×683mm
<b>Package Size(W*D*H)</b>	560×668×858mm