

Laboratory Refrigerator



Technical Parameters

Model		BPR-5V650	BPR-5V1008
Type (Shelf/Drawer)		5 layers/10 shelves	
Material		Plastic-coated steel wire	
Refrigeration Mode		Air-cooled	
Defrosting Mode		Automatic	
Refrigeration/g		R134a, CFC free/175g	
Noise		60dB(A)	
Ambient Temp.		10~32℃	
Temp. Range		5±3℃	
Temp. Accuracy		0.1℃	
Evaporator		Copper tube and aluminum fin	
Condenser		Bundy tube condenser	
Sensor		NTC	
Thermostat		Electronic thermostat	
Door		Electric-heating glass door	
Probe Access Port	Number	1	
	Position	Right	
	Inner Diameter	φ23	
Lamp		LED	
Display		LED	
Interface		USB	
Power Supply		220V, 50/60Hz; 110V, 60Hz	
Consumption		537W	
Current		3.2A	
Internal Material		Sprayed steel plate	
External Material		Sprayed steel plate	
Insulation Material		Foamed polyurethane cyclopentane	
Capacity		628L	968L
Standard Accessories		High and low temperature alarm, Power fault alarm, Thermostat fault alarm, Door door alarm, LED lamp, USB port, Probe access port	
Optional Accessories		Printer	
Net Weight		189kg	212kg
Gross Weight		235kg	262kg
Internal Size(W*D*H)		1100*454*1339mm	1100*684*1351mm
External Size(W*D*H)		1220*630*1885mm	1220*860*1885mm
Package Size(W*D*H)		1340*750*2100mm	1340*980*2100mm