

Laboratory Refrigerator



Technical Parameters

| | | |
|-----------------------|---|-------|
| Model | BPR-5V368 | |
| Type (shelf / drawer) | 5 layers shelves | |
| Material | Plastic-coated steel wire | |
| Refrigeration Mode | Air-cooled | |
| Defrosting Mode | Automatic | |
| Refrigerant/g | R600a, CFC free/35g | |
| Noise | 55dB(A) | |
| Ambient Temp. | 10~32°C | |
| Temp. Range | 5±3°C | |
| Temp. Accuracy | 0.1°C | |
| Evaporator | Copper tube and aluminum fin | |
| Condenser | Bundy tube | |
| Sensor | NTC | |
| Thermostat | Electronic thermostat | |
| Door | Electric heating glass door | |
| Probe access port | Number | 1 pcs |
| | Inner Diameter | φ23 |
| Display | LED | |
| Interface | USB | |
| Power Supply | 220V/50Hz | |
| Power | 230W | |
| Current | 1.65A | |
| Internal Material | Rolled aluminum board | |
| External Material | Spray steel plate | |
| Lagging | Foamed polyurethane cyclopentane | |
| Volume | 368L | |
| Standard Accessories | High and low temperature alarm, Power fault alarm, Thermostat fault alarm, Door open alarm, LED lamp, USB port, Probe access port | |
| Optional Accessories | Printer | |
| Net Weight | 76kg | |
| Gross Weight | 82kg | |
| Internal Size(W*D*H) | 566×475×1290mm | |
| External Size(W*D*H) | 650×600×2010mm | |
| Package Size(W*D*H) | 720×680×2040mm | |