

Petroleum Products Density Tester



Features:

- * This instrument is a kind of all-in-one machine. The control box adopts humanized design. The control switch adopts light-touch mode. Its structure is simple and compact, easy to operate.
- * It adopts intelligent LCD temperature controller. The control rate is fast and overstrike is small. The temperature control can reach $\pm 0.2^{\circ}\text{C}$.
- * It equips a hard glass vessel and electric stirrer. The temperature in vessel is uniform. Easy to observe the sample.

Technical Parameters:

| | | |
|--|--------------------------------|---------------------------|
| Model | BK-PPDT1884 | |
| Dimension of Constant Temperature Bath | $\Phi 300 \times 340\text{mm}$ | |
| Capacity of Cylinder | 500ml | |
| Temperature Controller | Range | RT+5~100°C |
| | Accuracy | $\pm 0.2^{\circ}\text{C}$ |
| | Sensor | Pt100 |
| Working Environment | Temperature | 15~35°C |
| | Relative Humidity | $\leq 85\%$ |
| Total Power Consumption | 1800W | |
| Dimension (L*W*H) | 560*380*580mm | |
| Power Supply | AC220V, 50Hz | |
| Package Size (L*W*H) | 690*700*765mm | |
| Net Weight | 37.5kg | |
| Gross Weight | 42.5kg | |