

## Small Capacity Thermostatic Shaking Incubator

### Features:

- \* Alarm system
  - \* Power-off memory
  - \* Intelligent interaction
  - \* 7-inch large LCD screen, displaying temperature and rotation speed in real time.
  - \* Historical data, curves and alarm records can be queried. Data can be saved and exported.
- It supports switching between Chinese and English.



### Technical Parameters:

Model	BJPX-ST68B
Controller	P.I.D
Control Mode	Standard mode; Program control mode: (Multi-steps rotate speed, temperature and time control)
Circulation Mode	Forced convection
Shaking Mode	Rotary shaking
Display	7-inch LCD touch screen
Data	Internal storage
Rotating Frequency	50~250rpm
Vibration Range	Φ26mm
Rotating Accuracy	±1rpm
Max. Capacity	100ml*23 or 250ml*15 or 500ml*9 or 1000ml*6 or 2000ml*4
Standard Capacity	500ml*9
Timing Range	0~999h/min
Temp. Range	RT+5~50°C
Temp. Accuracy	±0.1°C
Temp. Uniformity	±1°C (at 37°C)
Shaking Plate	1pc, 450*410mm
Consumption	500W
Power Supply	AC90V~240V; 50~60Hz
Optional Accessories	Mobile phone remote control program, UV lamp, Lighting lamp, Shaking plate, USB port
Function	Professional side air vents meet the oxygen demand of samples. Temperature-limiting alarm prevents damage from high temperature. High-definition glass door is convenient for viewing. It has the function of a safety door.
External Size (W*D*H)	750*570*550mm
Internal Size (W*D*H)	500*450*350mm
Package Size (W*D*H)	867*702*771mm
Net Weight	60kg
Gross Weight	92kg