

Small Capacity Thermostatic Shaking Incubator



Features:

- * Intelligent interaction
- * Power-off memory
- * Alarm system

Technical Parameters:

Model	BJPX-ST80B
Controller	P.I.D
Control Mode	Standard mode; Program control mode: (Multi-steps rotate speed, temperature and time control)
Display	Forced convection
Shaking Mode	Rotary shaking
Display	7-inch CTP
Data	Internal storage
Rotating Frequency	Φ26mm/35~300rpm
Rotating Accuracy	±1rpm
Max. Capacity	100ml*23 or 250ml*15 or 500ml*6 or 2000ml*4
Standard Capacity	50ml*5、100ml*5、250ml*4、500ml*3
Timing Range	0~999h/min
Temp. Range	4~65℃
Temp. Accuracy	±0.1℃
Temp. Uniformity	±1℃ (at 37℃)
Shaking Plate	1pcs, 450*410mm
Volume	80L
Consumption	650W
Power Supply	AC220V~240V; 50~60Hz
Optional Accessories	Shaker remote control program, UV lamp, Lighting lamp, Shaking plate, USB port
Auxiliary Function	Timing for per-heating and refrigerating, Ultra-low speed start, Monitoring timer, parameter memory, Power-off memory, Auto defrosting, Safety door, Setting parameters checking, History memory, Monitoring temperature and environmental temperature for correction
External Size (W*D*H)	720*700*580mm
Internal Size (W*D*H)	500*450*350mm
Net Weight	90kg
Gross Weight	115kg
Package Size (W*D*H)	822*855*750mm