

Static Storage Liquid Nitrogen Container



YDS-10S(6)
/YDS-10-80S(6)
/YDS-10-125S(6)



YDS-10
/YDS-10-80
/YDS-10-125



YDS-20S(6)
/YDS-30S(6)
/YDS-30-80S(6)
/YDS-30-125S(6)
/YDS-35S(6)
/YDS-35-80S(6)
/YDS-35-125S(6)



YDS-20
/YDS-30
/YDS-30-80
/YDS-30-125
/YDS-35
/YDS-35-80
/YDS-35-125

Features:

- * High vacuum, multi-layer thermal insulation design
- * Low static evaporation rate, ultra-low evaporation loss
- * Made of high-quality alloy aluminum
- * Vacuum warranty for 5 years
- * Optional liquid level ruler

Technical Parameters:

Model	Capacity	Empty Weight	Caliber	Outer Diameter	Height	Static Evaporation Loss	Static Holding Time	Canister Height	Canister No.(Standard)	Canvas Protective Sleeve	Lockable Lid	Packing Size	Gross Weight
Unit	L	kg	mm	mm	mm	L/d	d	mm	pc	pc	set	mm	kg
YDS-10 S(6)	10	6.2	50	303	550	0.12	86	120	6	√	√	356*356*620	8.35
YDS-10 -80S(6)	10	6.2	80	303	555	0.18	57	120	6	√	√	356*356*620	8.5
YDS-10 -125S(6)	10	6.5	125	303	575	0.33	30	120	6	√	√	356*356*620	8.8
YDS-10 -125S(6)	10	6.5	125	303	505	0.33	30	120	6	√	√	356*356*620	8.8
YDS-10 -80	10	6.4	80	303	505	0.18	57	120	6	√	√	356*356*620	8.7
YDS-10 S(6)	10	6.2	50	303	530	0.12	86	120	6	√	√	356*356*620	7.5
YDS-10 -80S(6)	10	6.2	80	303	555	0.18	57	120	6	√	√	356*356*620	8.5
YDS-10 -125S(6)	10	6.5	125	303	575	0.33	30	120	6	√	√	356*356*620	8.8
YDS-10 -125	10	6.5	125	303	505	0.33	30	120	6	√	√	356*356*620	8.8
YDS-20 S(6)	20.1	11.2	50	409	650	0.12	168	120	6	√	√	457*457*720	13.2
YDS-20 -80S(6)	20.1	9.9	50	409	650	0.12	168	120	6	√	√	457*457*720	11.9
YDS-20 -125S(6)	20.1	12.9	50	455	670	0.12	251	120	6	√	√	502*502*765	14.9
YDS-20 -80S(6)	20.1	12.9	50	455	620	0.12	251	120	6	√	√	502*502*765	14.9
YDS-20 -80	20.1	13.2	80	455	680	0.21	145	120	6	√	√	502*502*765	15.2
YDS-20 -125S(6)	20.1	14	125	455	685	0.35	90	120	6	√	√	502*502*765	16
YDS-20 -125	20.1	14	125	455	625	0.35	90	120	6	√	√	502*502*765	16
YDS-30 S(6)	31.5	13.8	50	475	680	0.125	278	120	6	√	√	502*502*765	15.8
YDS-30 -80S(6)	31.5	13.8	80	475	685	0.22	155	120	6	√	√	502*502*765	15.8
YDS-30 -80	31.5	13.8	80	475	630	0.125	278	120	6	√	√	502*502*765	15.8
YDS-30 -125S(6)	31.5	13.8	125	475	685	0.22	155	120	6	√	√	502*502*765	15.8
YDS-30 -125	31.5	14	125	455	625	0.35	90	120	6	√	√	502*502*765	16
YDS-35 S(6)	35.5	14.1	50	475	690	0.125	278	120	6	√	√	502*502*765	15.8
YDS-35 -80S(6)	35.5	13.8	80	475	685	0.22	155	120	6	√	√	502*502*765	15.8
YDS-35 -80	35.5	13.8	80	475	630	0.125	278	120	6	√	√	502*502*765	15.8
YDS-35 -125S(6)	35.5	14.1	125	475	690	0.22	155	120	6	√	√	502*502*765	16.1
YDS-35 -125	35.5	14.1	125	475	630	0.37	95	120	6	√	√	502*502*765	16.1