

Table Top Low Speed Centrifuge



Features:

- * Microcomputer control, large screen color LCD, full touch screen operation interface
- * Brushless AC variable frequency motor drive
- * Double door cover lock system, ensure running safety
- * Provide 20 kinds of working program storage, easy to use and improve work efficiency
- * Provide 15 kinds of acceleration/deceleration
- * It has two timing functions: setting and jog
- * Differential centrifugation: five differential centrifugation procedures are reserved
- * Double layer steel structure, spray anti-corrosion coating surface of centrifugal chamber
- * Automatic balance and unbalance protection
- * Soft braking function, it can effectively prevent sample resuspension and protect sensitive samples
- * Countdown function: the countdown in seconds, real-time display of remaining working time
- * The centrifuge can customize 485 communication interface function and operate through remote control
- * Sunken exhaust passage, it can prevent aerosol pollution during centrifugation

Technical Parameters:

Model	JW-2002
Max. Capacity	12*15ml
Max. Speed	5000rpm
Max. RCF	3130xg
Speed Precision	±10rpm
Timing Range	1s~99h59min59s/jog
Noise	≤50dB
Power Supply	AC220V, 50/60Hz(standard); AC110V, 50/60Hz(optional): External transformer
External Size(W*D*H)mm	426*322*340
Package Size(W*D*H)mm	480*425*475
Gross Weight(kg)	33

Rotor for JW-2002:

No.	Rotor	Max. Capacity	Max. Speed(rpm)	Max. RCF(*g)
No.1	Angle Rotor	12*10/15ml	5000	3130