

Thermostatic Shaking Water Bath



Application:

Suitable for BOD measurement in water analysis, cultivation and preservation of bacteria, viruses, molds, and microorganisms, plant cultivation, breeding experiments, and other applications.

Features:

- * Shaking speed: 40~300 rpm.
- * Temperature control range: RT+5°C to 100°C, with rapid heating.
- * LED display, independent control of temperature and speed.
- * Selectable timed or continuous operation mode.
- * Inner chamber made of 304 stainless steel, rust-resistant and easy to clean.
- * Comes standard with a universal spring clamp.

Technical Parameters:

Model	BK-WBS30C	BK-WBS30R
Amplitude	20mm	
Oscillation	Rotatory shaking	Reciprocating shaking
Display	LED	
Speed Range	40~300rpm	
Temperature Control Range	RT+5°C~100°C	
Temperature Control Accuracy	±0.5°C	
Timing Range	1~9999min/Continuous	
Standard Tray Configuration	1 pc, universal spring clip	
Tray Size	410*310mm	
Max Load	20kg	
Consumption	1500W	
Power Supply	Standard: AC220V, 50/60Hz; optional: AC110V, 50/60Hz	
External Size(W*D*H)	715*550*490mm	
Package Size(W*D*H)	770*625*580mm	
Net Weight	34kg	
Gross Weight	40kg	