

Thermostatic Water Tank



Features:

- * All-round heating, rapid temperature rise, adjustable lid locking temperature, constant temperature operation, making the experiment accurate.
- st OLED display, temperature, time and other parameters displayed in real time.
- * Intelligent algorithm monitoring, water shortage stops heating when turned on, and the working time of the instrument can be freely set.
- * The water tank is stamped and formed from stainless steel, which is resistant to high temperatures, corrosion, and rust; it is equipped with a load-bearing frame.

Technical Parameters:

Model	BK-W2	BK-W4	BK-W6
Туре	1 row, 2 holes	2 rows, 4 holes	2 rows, 6 holes
Heating Power	600W	1000W	1500W
Chamber	Stainless steel		
Temp. Range	RT~100℃		
Temp. Fluctuation	±0.5℃		
Display	OLED		
Timing	Yes		
Capacity	5L	10L	20L
Power Supply	Standard: 220V 50/60Hz, optional: 110V 50/60Hz		
Chamber Size	300*150*150mm	325*300*145mm	505*300*150mm
External Size	385*280*275mm	385*420*275mm	570*420*275mm
Net Weight	6.15kg	7.85kg	11.3kg
Packing Size	444*294*324mm	444*444*324mm	634*444*324mm
Gross Weight	7.8kg	10.5kg	13.6kg