

Ultrasonic Cleaner



Introduction:

Ultrasonic cleaner is a non-polluting, non-damaging, multi-purpose cleaning equipment. It not only has a powerful cleaning effect on objects with complex shapes, but also accelerates dissolution and emulsification. Ultrasonic cleaner has the unparalleled advantages of other physical cleaning or chemical cleaning, and is widely used in service industry, electronics industry, pharmaceutical industry, laboratory, machinery industry, cemented carbide industry, chemical industry and other fields.

Features:

- * Standard accessories: soundproof cover, basket, PVC pipe.
- * The shell and inner cavity are made of 304 stainless steel, which is anti-corrosion.
- * LED display for BK-VAD series.

Technical Parameters:

Model	BK-180VAD	BK-240VAD	BK-360VAD	BK-480VAD	BK-600VAD
Capacity(L)	6.5	10	15	22.5	30
Ultrasonic Frequency	Double Frequency, 28/40kHz				
Time Range/ Heating Temperature	1-99min/RT~80℃				
Ultrasonic Power	180W	240W	360W	480W	600W
Heating Power	500W				
Power Supply	220V 50Hz				
Tank Size(mm)	300*150*150	300*240*150	330*300*150	500*300*150	500*300*200
External Size(mm)	330*180*310	330*270*310	360*330*310	530*330*310	530*330*350
Packing Size(mm)	440*280*355	440*360*355	475*415*380	640*415*380	640*415*425
Gross Weight(kg)	7	9	11	14	17

Ultrasonic Cleaner



Introduction:

Ultrasonic cleaner is a non-polluting, non-damaging, multi-purpose cleaning equipment. It not only has a powerful cleaning effect on objects with complex shapes, but also accelerates dissolution and emulsification. Ultrasonic cleaner has the unparalleled advantages of other physical cleaning or chemical cleaning, and is widely used in service industry, electronics industry, pharmaceutical industry, laboratory, machinery industry, cemented carbide industry, chemical industry and other fields.

Features:

- * Standard accessories: soundproof cover, basket, PVC pipe.
- * The shell and inner cavity are made of 304 stainless steel, which is anti-corrosion.
- * LED display for BK-AD series.

Technical Parameters:

Model	BK-180AD	BK-240AD	BK-360AD	BK-480AD	BK-600AD
Capacity(L)	6.5	10	15	22.5	30
Ultrasonic Frequency	Single Frequency, 40kHz				
Time Range/ Heating Temperature	1-99min/RT~80℃				
Ultrasonic Power	180W	240W	360W	480W	600W
Heating Power	500W				
Power Supply	220V 50Hz				
Tank Size(mm)	300*150*150	300*240*150	330*300*150	500*300*150	500*300*200
External Size(mm)	330*180*310	330*270*310	360*330*310	530*330*310	530*330*350
Packing Size(mm)	440*280*355	440*360*355	475*415*380	640*415*380	640*415*425
Gross Weight(kg)	7	9	11	14	17