

## Height and weight tester

### Product Features:

- \* Piezoelectric strain ultrasonic probe for touch-free, high-efficiency height measurement
- \* Well-known brand, industrial grade, high-precision resistance strain weighing sensor to measure weight
- \* High-precision, anti-magnetic, anti-noise, ultra-optimized moisture-proof circuit design, microcomputer programming, automatic calculation of BMI value
- \* Silent period (standby) automatically displays the time, date, and ambient temperature
- \* Multilingual voice operation guidance, real-time broadcast of measurement results
- \* Temperature automatic compensation function
- \* RS-232 data output interface
- \* Aluminum alloy body, steel structure chassis process, super wear-resistant and non-slip ABS pedal
- \* Foldable + mobile rollers to meet a variety of application scenarios
- \* Can realize personalized expansion and customization requirements (blood pressure, Bluetooth, remote control, etc.)
- \* Support enterprise groups, chain institutions and health all-in-one machine project supporting plans
- \* Worry-free after-sales (365 days \* 24 hours) quality assurance for one year (except printers)



### Main Functions:

| Model     | weight       | height            | screen                    | Print                      |
|-----------|--------------|-------------------|---------------------------|----------------------------|
| BK-HGM700 | weigh sensor | ultrasound sensor | LCD (Chinese and English) |                            |
| BK-HGM701 | weigh sensor | ultrasound sensor | LCD (Chinese and English) | Multilingual Word printing |
| BK-HGM702 | weigh sensor | ultrasound sensor | LED (Chinese and English) |                            |

| Model     | voice               | move pay | remote control | Bluetooth | data output       |
|-----------|---------------------|----------|----------------|-----------|-------------------|
| BK-HGM700 | multi-country voice | optional | optional       | optional  | serial port RS232 |
| BK-HGM701 | multi-country voice | optional | optional       | optional  | serial port RS232 |
| BK-HGM702 | multi-country voice | optional | optional       | optional  | serial port RS232 |

### Technical Parameters:

| Model                       | BK-HGM700                         | BK-HGM701 | BK-HGM702 |
|-----------------------------|-----------------------------------|-----------|-----------|
| Height Measuring range      | 60-200cm                          |           |           |
| division value              | 0.5cm                             |           |           |
| weight Measuring range      | 2-300kg                           |           |           |
| division value              | 0.1kg                             |           |           |
| working voltage             | AC110-220V 50/60HZ                |           |           |
| Overall height              | 231cm                             |           |           |
| folding height              | 123cm                             |           |           |
| Weight of the whole machine | net weight:16kg gross weight:20kg |           |           |
| Measurement speed           | 480 times/hour                    |           |           |
| data transmission           | RS232 serial port                 |           |           |
| Package size                | 600*410*140 1270*310*300mm        |           |           |
| standby power               | ≤4W                               |           |           |