

NAKKA Environmental Appliance Technology Co., Ltd Add: No.3 Zhongjian road, zhongyong industrial area, Leliu Town, Foshan City, Guangdong Province

Tel: 86-0757-25556223 E: nakka@nakka.cn

www.nakka.net



The Choice Of Life

DC Frequency Conversion Fan

Bionic Natural Wind



COMPANY PROFILE

NAKKA Smart DC Technology and products is a manufacturing enterprise that focuses on production and development of high technology smart appliances primarily with household floor fans, commercial, industrial and ventilation fans.

With a quality oriented attitude, innovative and pragmatic spirit of research and development within the Research and Development team our company has successfully developed and patented a DC (Direct Current) motor fan to be an industry leader. What makes this DC motor unique is it is more energy efficient, low noise, smooth operation which allows NAKKA products to last longer than other electric fans.



www.nakka.net

THE CHOICE OF LIFE

NAKKA

OUR CERTIFICATION

<section-header><section-header><section-header></section-header></section-header></section-header>	<section-header><section-header><section-header><section-header><section-header><section-header><section-header><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></section-header></section-header></section-header></section-header></section-header></section-header></section-header>	<image/>	<text></text>	<text></text>
<text></text>		<text><text><text><text><text><text></text></text></text></text></text></text>	<image/> <section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><text><text><text><text></text></text></text></text></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header>	<section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header>



(C) CE
















The Precision Of
 Grinding Is 0.02mm


Fully Sealed Smart DC Motor

Moisture proof | Dust-proof | Energy conservation | Long-lasting

Energy Consumption Of Industrial Fan Per Month



• Technical Bearings Of Japan Seiko







100% Enamelled Wire


DC motor

Sine Wave Schematic Diagram

The sine wave noise reduction technology makes the motor work more quiet.







NNKP

Double Ring Spiral Wind More Gentle Natural Wind Sense

Inside and outside double layer knob wind channel, like a trumpet-type wind channel for an all around even spread of the wind.

The true sense of natural wind.

DC




850rpm/min





Time



18 Blades Design Mute Technique

Wide-angle Air Supply

Wide-angled shaped air supply angle is up to 120 degrees enables every person in the room, where ever located enjoy the cool breeze and feel from theEC fan.

200







Remote Control

Wireless remote control uses 433Hz radio remote control technology. The Smart DC fan can effectively be controlled over 20 meters in an open area.

Equipped with a magnetic device for easy storage on the face of the DC fan.

4

U

•

C

RF Remote Control Air Volume Down

Unique Remote Control holder design





Multi-protection System

Overcurrent protection | Overvoltage protection | Motor blockage protect Patented Fan Grill Net Cover with a circular structure, double-track sided frame with safety lock for additional protection for smaller hands and fingers



Vice line diameter



Line spacing

(+ 18m) + 18m

Main line diameter

✓ + 8mm





A Quiet Time That Is Not Disturbed

Undisturbed And Peaceful Sleep Operating With Low Noise, Soft And Quiet.

The combination of gentle and natural wind and a comfortable environment makes you feel as if you are in nature.

NNKP 20

Intelligent Timer Setting

An automatic shutdown time up to 9 hours, depending on your current room environment to ensure a more comfortable experience.



3 Different Type Of Wind Function 6 Levels Of Wind Speed





Swing Light Natural Wind Light Sleep Mode Light Air Volume SPEED Up Air Volume SPEED Down 0 TIMER Timer SLEEP Sleep Mode

NNKN









Smart DC Commercial Fan Series





CE BOHS ERP RED

Model: FS45-DC17ARL



Size	18 inch (450mm)		
Rated power	18W-90W		
Rated voltage(V)	200-240	200-240V/100-120V	
Maximum wind volume	167 m³/min		
Fan sound power level	56db		
Adjustable in height	108-1	135cm	
Left&right air supply angle	9	0°	
Up&down air supply angle	35°		
Controler frequency	433Hz		
		11 6kg	
Gross weight	11.6kg		
Net weight	9.7kg		
Packing size	52*35*53cm	73.5*19.5*52.5cm	
20 GP capacity	256	419	
40 GP capacity	520	838	
40 HC capacity	604	959	



Model: FS45D-DC17ARL



Size	18 inch (450mm)*2
Rated power	18W-180W
Rated voltage(V)	200-240V/100-120V
Maximum wind volume	167*2 m³/min
Fan sound power level	56*2 db
Adjustable in height	155-170cm
Left&right air supply angle	90°
Up&down air supply angle	35°
Controler frequency	433Hz
Gross weight	20.8kg
Net weight	18.1kg
Packing size	83*24.5*54cm
20 GP capacity	252
40 GP capacity	508
40 HC capacity	568





Model: FM45-DC17ARL

CE BOHS ERP RED



Size	18 inch (450mm)
Rated power	18W-160W
Rated voltage(V)	200-240
Maximum wind volume	167 m³/min
Fan sound power level	56db
Water tank volume	2 liter
Continuous spray	5-8 hours
Effective area	20 m
Spray droplet	0.05-0.20mg
Controler frequency	433Hz
Gross weight	14.5kg
Net weight	12kg
Packing size	52*50*52cm
20 GP capacity	176
40 GP capacity	384
40 HC capacity	480



Model: FS45-DC17BL / FS50-DC17BL



	FS45-DC17BL	FS50-DC17B
Size	18 inch (450mm)	20 inch (500mi
Rated power	4W-90W	4W-90W
Rated voltage(V)	200-240V	/100-120V
Maximum wind volume	167 m³/min	167 m³/min
Fan sound power level	63db	63db
Adjustable in height	108-1	135cm
Left&right air supply angle	90°	
Up&down air supply angle	3	5°
Gross weight	10.8kg	12kg
Net weight	8.9kg	10.3kg
Packing size	73*19*52.5cm	79*20*58cm
20 GP capacity	367	287
40 GP capacity	818	660
40 HC capacity	884	715





Model: FTS45-DC17ARL

CE BOHS ERP RED





Ø Safety Refinements

DC Motor

Energy conservation







Size	18 inch (450mm)
Rated power	18W-90W
Fan sound power level	56db
Adjustable in height	58cm
Left&right air supply angle	90°
Up&down air supply angle	35°
Controler frequency	433Hz
Gross weight	11.6kg
Net weight	9.7kg
Packing size	73.5*19.5*52.5cm

Rated voltage(V)	200-240V/100-120V
Maximum wind volume	167 m³/min
20 GP capacity	419
40 GP capacity	838
40 HC capacity	959

Model: FTS45-DC17BL





Strong wind Mute

DC

DC Motor

Ø

Energy conservation

Safety Refinements

RF CONTROL



(Optional)

Size	18 inch (450mm)
Rated power	4W-90W
Fan sound power level	63db
Adjustable in height	58cm
Left&right air supply angle	90°
Up&down air supply angle	35°
Gross weight	11.6kg
Net weight	9.7kg
Packing size	73*19*52.5cm



Rated voltage(V)	200-240V/100-120V
Maximum wind volume	167 m³/min
20 GP capacity	367
40 GP capacity	818
40 HC capacity	884



Model: FW45-DC17ARL

CE BOHS ERP RED





Ø

DC Motor





Safety Refinements







Size	18 inch (450mm)
Rated power	18W-90W
Fan sound power level	56db
Left&right air supply angle	90°
Up&down air supply angle	35°
Controler frequency	433Hz
Gross weight	10.8kg
Net weight	8.9kg
Packing size	52.5*27.5*53.5cm

Rated voltage(V)	200-240V/100-120V
Maximum wind volume	167 m³/min
20 GP capacity	352
40 GP capacity	792
40 HC capacity	896

Model: FW45-DC17BRL







Strong wind

DC Motor

Ø

Energy conservation

Safety Refinements

3

RF REMOTE CONTROL




Size	18 inch (450mm)
Rated power	4W-90W
Fan sound power level	63db
Left&right air supply angle	90°
Up&down air supply angle	35°
Controler frequency	433Hz
Gross weight	10.8kg
Net weight	8.9kg
Packing size	52.5*27.5*53.5cm



Rated voltage(V)	200-240V/100-120V
Maximum wind volume	167 m³/min
20 GP capacity	352
40 GP capacity	792
40 HC capacity	896

Smart DC Industrial Fan Series





Science and Electronic Technology

Using high-torque synchronous motor electronic control Technology, the swing of the head angle can be freely controlled.

The plate bearing is included in the design to support the main patented DC motor, Which greatly reduces the friction generated by the fan pendulum so that the synchronous motor has less stress and prolongs the service life of NAKKA smart DC commercial and industrial fans.



Model: FS75-DC17ARL


 DC Motor
 Strong wind
 Mute
 Remote Control
 Energy conservation
 Safety Refinements

Performance

- Pole Adjustable pole
- Base 8kg plastic pedestal (can past 12" ramp testing)
- Grill 30 inch 24 lines strong grill (pass the finger testing)
- Blade 30 inch 3 blades Aluminum design (lowest noise , max air volume)
- Power Cable 3*0.75mm 100% copper power line(The length of the power cord is 1.8m)

Size	30 inch (750mm)
Rated power	25W-130W
Rated voltage(V)	200-240V/100-120V
Maximum wind volume	314.6m ³ /min
Fan sound power level	72db
Left&right air supply angle	75°
Up&down air supply angle	40°
Adjustable in height	151-168cm

Gross weight	2	24kg
Net weight	21	1.2kg
Packing size	25* 52.5*	*8*82.5cm 19*32cm 8.5*52.5cm *7*98cm
One fan one container	85*20.	5*85cm
20 GP capacity	300	172
40 GP capacity	650	324
40 HC capacity	740	408



Model: FS65-DC17BL



Performance

Pole	Adjustable pole
Base	7kg plastic pedestal (can past 12" ramp testing)
Grill	26 inch 16 lines strong grill (pass the finger testing)
Blade	26 inch 3 blades Aluminum design (lowest noise , max air volume)
Power Cable	3*0.75mm 100% copper power line(The length of the power cord is 1.8m)

Size	26 inch	(650mm)
Rated power	20W	-130W
Rated voltage(V)	200-240\	//100-120V
Maximum wind volume	251 r	n³/min
Fan sound power level	6	3db
Left&right air supply angle	7	75°
Up&down air supply angle	2	10°
Adjustable in height	145-	162cm
Gross weight	20	.7kg
Net weight	18	.7kg
Packing size	25*19 52.5*8.	*72cm 9*32cm 5*52.5cm '98cm
One fan one container	97*21	*73cm
20 GP capacity	350	198
40 GP capacity	730	402
40 HC capacity	830	473





Model: FW75-DC17ARL

DC 3 Ø (@ |X motor Remote Control Energy Safety conservation Refinements DC Motor Strong wind Mute

Performance Grill 30 inch 24 lines strong grill (pass the finger testing) Blade 30 inch 3 blades Aluminum design (lowest noise , max air volume) Power Cable 3*0.75mm 100% copper power line(The length of the power cord is 1.8m)

Size	30 inch (750mm)
Rated power	25W-130W
Rated voltage(V)	200-240V/100-120V
Maximum wind volume	251 m³/min
Fan sound power level	58db
Left&right air supply angle	75°
Up&down air supply angle	40°

Gross weight	14	.14kg
Net weight	11	.9kg
Packing size		*8*82.5cm *19*32cm
One fan one box	85*20.	5*85cm
20 GP capacity	435	180
40 GP capacity	900	376
40 HC capacity	1000	471





Model: FW65-DC17ARL



Performance

Grill	26 inch 12 lines strong grill
Blade	26 inch 3 blades Aluminum design (lowest noise , max air volume)
Power Cable	3*0.75mm 100% copper power line(The length of the power cord is 1.8m)

Size	26 inch	(650mm)
Rated power	20W	-130W
Rated voltage(V)	200-240	//100-120V
Maximum wind volume	251 г	m³/min
Fan sound power level	6	3db
Left&right air supply angle	7	75°
Up&down air supply angle	2	10°
Gross weight	10.	72kg
Net weight	9.	65kg
Packing size	. = •	*72cm 19*32cm
One fan one box	97*21*	73cm
20 GP capacity	535	198
40 GP capacity	1110	402
40 HC capacity	1250	473











Model: FD60-DC20ARL-P



IP54 WATERPROOF Fan

Size	24 INCH
Rated power	150W
Rated voltage(V)	200-240V/100-120V
Oscillation Degree	360°
Control panel	touched control panel
Fan mode	6 wind speeds, 9h timer, strong wind mode

Gross weight	16.65kg
Net weight	14.9kg
Packing size	94.5*24*96cm

24" 30" 36" 42" 48" **Optional Size**





Model: FW50-DC20ARL-P



IP54 WATERPROOF Fan

Size	20 INCH
Rated power	135W
Rated voltage(V)	200-240V/100-120V
Oscillation Degree	360°
Control panel	touched control panel
Fan mode	6 wind speeds, 9h timer, strong wind mode

Gross weight	7.8kg
Net weight	6.6kg
Packing size	62*20*63cm

20 GP capacity	369
40 GP capacity	768
40 HC capacity	929











Model: FW40-DC22ARL



Size	16 INCH
Rated power	28W
Rated voltage(V)	200-240V/100-120V
Control panel	touched control panel
Fan mode	9 wind speeds, 9h timer, strong wind mode, sleep mode, natural wind mode
Gross weight	4.13 kg
Net weight	3.13 kg
Packing size	49*17*58cm
Rotate speed	
20 GP capacity	626
40 GP capacity	1290
40 HC capacity	1476



Model: FS40-DC22ARL



Size	16 INCH
Rated power	30W
Rated voltage(V)	200-240V/100-120V
Control panel	touched control panel
Fan mode	9 wind speeds, 9h timer, strong wind mode, natural wind mode
Maximum wind volume	68m³/s

Gross weight	6.62kg
Net weight	5.73kg
Packing size	59*16*46.5cm
Rotate speed	1-550rpm 4-900rpm 2-700rmp 5-1050rpm 3-750rpm 6-1200rpm
20 GP capacity	600
40 GP capacity	1420
40 HC capacity	1500

Control Panel Speed Indicators Remote Receiver Mode Indicators

Power Key Speed Key Timer Indicators Timer Key Oscillation Key

DC Frequency Conversion Fan





INFRARED



