

Chibi Zhilixing Electronic Technology Co., Ltd.

Display Port 1.4 Active Optical Cable

DP 1.4, DP signal, 100m transmission distance, no signal attenuation, anti-EMI



32.4Gbps	HDCP2.2	3D	HDR
----------	---------	----	-----

Name	Display port 1.4 Active Optical Cable		
Model No.	GQ-19-101		
Resolution	8K@60Hz,4K@144Hz		
Bandwidth	32.4Gbps		
Chip	Imported photoelectric conversion chip		
Color space	4:4:4 Max		
Color depth	12 bit Max		
Туре	Male - Male		
Core	4-core fiber + 7-core tinned copper		
Outer diameter	5.2mm		
Shell	Zinc alloy		
Jacket	PVC, RoHS Directive-compliant		
Power supply	No external power supply required, plug and play		
Support	HDCP 2.2/HDR/EDID/DDC/3D		
Power consumption.	500mW		
Working temperature	-40°C~70°C		

FEATURE

1, Compatible with all Displayport 1.4 Standard devices.

2, Compatible with all Displayport 1.4 Standard devices.

3, Four-core optical fiber transmits DP signals, Seven--core tinned copper transmits signaling protocol. Anti-electromagnetic interference, No attenuation.

4, Support long transmission distance, the longest over 100 meters.

5, Photoelectric conversion chip to improve compatibility, stability and service life.

6, Plug and play, no need external power support, no drivers program required


7, Zinc alloy shell Anti-electromagnetic interference increase wear resistance and improve service life.

8, Compact zinc alloy shape, more suitable for pipe wiring.

SUPPORT



DETAILS



APPLICATION

Г

ENGINEERING DRAWING



1, Large screen display multimedia display control system.

- 2, Remote flat-panel TV.
- 3, Medical image display.
- 4, large outdoor advertising screens.
- 5, Public security HD camera.
- 6, High-definition long-distance video conferencing.
- 7, Large poster. Home theater.
- 8, High-defintion digital bulletin board.
- 9, Family, school, monitoring, security.
- 10, Aviation aircraft video imaging system.
- 11, Splicing screen video display.


Displayport 1.4 Standard connector

Resolution support 4K@144Hz; 8K@60Hz; 4:4:4 Support 3D visual effects. Support DHCP 2.2,HDR 10,EDID,CEC,DDC,3D. Date rate:32.4Gbps bandwidth



	CUSTOM	SERVICES
--	--------	----------

Length	10~100 meter
Zinc Alloy Shell's color	Black/Silver/ Others
Rubber core's color	Black/Blue
Jacket	PVC/Braiding/Steel/CL3
Logo	Customizable for free
Packing	Customizable
Connector	Type A/Mini/Micro
Туре	Male/Female



PACKING

Lengh (meter)	Weight (kg)	Packaging	Packing size (cm)	Each box number (piece/box)	Each box weight (box/kg)
	0	Velcro tape+OPP bag	× /	ų ,	10.7
10m	0.34	venero tape vorr bag	39×33×26	30	10.7
20m	0.59	Velcro tape+OPP bag	39×33×26	25	12.5
30m	0.80	reel+box	46×22×41	10	11.9
40m	1.06	reel+box	46×22×41	10	14.5
50m	1.32	reel+box	46×22×41	10	17
60m	1.57	reel+box	45×22×30.5	4	8.4
70m	1.83	reel+box	45×22×30.5	4	9.8
100m	2.59	reel+box	45×22×30.5	4	13.5

CONTACT

Mr.Ryan Lei Tel/Whatsapp/Wechat:+86 13997531005

Email: rvan@cbzlx.com Website: www.cbzlx.com