

» C9370 BRAKE LATHE



Main specifications

Spindle Travel	9.875" (251mm)	Spindle Speed	70,88,118 RPM
Spindle Feed Speed	0.002" (0.05mm)–0.02" (0.5mm) Rev	Cross Feed Speed	0.002" (0.05mm)–0.01" (0.25mm) Rev
Handwheel Graduations	0.002" (0.05mm)	Rotor Diameter	7" –18" (180–457mm)
Rotor Thickness	2.85" (73mm)	Drum Diameter	6" –17.7" (152–450mm)
Drum Depth	9.875" (251mm)	Motor	110V/220V/380V 50/60Hz
Gross Weight	325KG	Dimension	1130 × 1030 × 1150 mm

Feature:

1. Quickly, accurately and efficiently cutting both drum and rotor.
2. Fast and slow setting.
3. Three kinds of speed to choose for spindle speed.
4. A convenient design to quickly change from rotor to drum.
5. Stop automatically after the cutting.



Standard Adapter

No.	Description	Part No.	Qty.
1	Taper Cone (45x70mm)	C4-00-44-03 (For 1" Arbor)	1
2	Taper Cone (59x75mm)	C4-00-44-04 (For 1" Arbor)	1
3	Taper Cone (66x82mm)	C4-00-44-05 (For 1" Arbor)	1
4	Taper Cone (74x90mm)	C4-00-44-06 (For 1" Arbor)	1
5	Clamp (94mm)	C4-00-46-01 (For 1" Arbor)	2
6	Clamp (116mm)	C4-00-46-02 (For 1" Arbor)	2
7	Clamp (146mm)	C4-00-46-03 (For 1" Arbor)	2
8	Spring	C4-00-45 (For 1" Arbor)	1
9	Open End Wrench (27–30mm)		1
10	Silencing Belt for Rotor and Drum	C4F-4-0 C4-12-0	2
11	Spacer	For 1" Arbor	6
12	Hub Localize (Arbor 2" /50.8 mm)	C8F-01-01	1
13	Localizer Big Taper Cone (79x108mm)	C8F-01-02 (For 2" Arbor)	1
14	Localizer Small Taper Cone (54x82.5mm)	C8F-01-03 (For 2" Arbor)	1
15	Nut	C8F-01-04 (For 2" Arbor)	1
16	Big Spacer (171.5mm)	C8F-02(For 2" Arbor)	1
17	Small Spacer (133mm)	C8F-03(For 2" Arbor)	1
18	Big Adapter (171.5mm)	C8F-04-00 (For 2" Arbor)	1
19	Small Adapter (133mm)	C8F-05-00 (For 2" Arbor)	1
20	Step Adapter (25.4x50.8mm)	C8F-06 (For 2" Arbor)	1
21	Bend Wrench 78–85mm		1