

» C9350C BRAKE LATHE



Main specifications

Spindle Travel	6.875" (175mm)	Spindle Speed	70,88,118 RPM
Spindle Feed Speed	0.002" (0.05mm)–0.02" (0.5mm) Rev	Cross Feed Speed	0.002" (0.05mm)–0.02" (0.5mm) Rev
Handwheel Graduations	0.002" (0.05mm)	Rotor Diameter	7" –15" (180–381mm)
Rotor Thickness	1.875" (48mm)	Drum Diameter	6" –17.7" (152–450mm)
Drum Depth	6.875" (175mm)	Motor	110V/220V/380V 50/60Hz
Gross Weight	290KG	Dimension	1010 × 950 × 1150mm

Feature:

1. DC motors designed to meet the demanding requirement of industrial motion control.
2. "Change Adapter" system to eliminate the need for conventional bell clamps and cones.
3. The precision twin cutter tools and a quick drum to rotor changeover to help increase your service capability.
4. Infinitely variable spindle and cross feed speed settings for quick rough and precision finish cuts.
5. Positive rake cutter tip angle provides for a one pass finish virtually every time, allowing you to complete your work fast.



Standard Adapter

No.	Description	Part No.	Qty.
1	Twin Cutter	C4-09-00	1
2	Arbor (1" /25.4mm) with nut, combination washer, flat washer and tie rod	C4-00-42/C4-00-48A/C4-05-00/C4-00-47	1
3	Plastic Safety Shield	C4-11-00	1
4	Open End Wrench (27–30mm)		1
5	Square Wrench		1
6	V Belt A610		1
7	Cutting Bar	C4-10-0C/C4-9-9-0C/C4-9-10-0C	3
8	Silencing Belt for Rotor and Drum	C4F-4-0 C4-12-0	2
9	Taper Cone (30x44mm)	C4-00-44-01 (For 1" Arbor)	1
10	Taper Cone (31x57mm)	C4-00-44-02 (For 1" Arbor)	1
11	Taper Cone (45x70mm)	C4-00-44-03 (For 1" Arbor)	1
12	Taper Cone (59x75mm)	C4-00-44-04 (For 1" Arbor)	1
13	Taper Cone (66x82mm)	C4-00-44-05 (For 1" Arbor)	1
14	Taper Cone (74x90mm)	C4-00-44-06 (For 1" Arbor)	1
15	Taper Cone (85.8x103mm)	C4-00-44-07 (For 1" Arbor)	1
16	Double Taper Cone 1.34" x1.66" (34x42mm)	C4-00-44-8	1
17	Double Taper Cone 1.36" x1.69" (35x43mm)	C4-00-44-9	1
18	Double Taper Cone 1.72" x2.06" (44x52mm)	C4-00-44-10	1
19	Double Taper Cone 2.06" x2.44" (52x62mm)	C4-00-44-11	1
20	Double Taper Cone 2.45" x2.81" (62x71mm)	C4-00-44-12	1
21	Spring	C4-00-45 (For 1" Arbor)	1
22	Clamp (94mm)	C4-00-46-01 (For 1" Arbor)	2
23	Clamp (116mm)	C4-00-46-02 (For 1" Arbor)	2
24	Clamp (146mm)	C4-00-46-03 (For 1" Arbor)	2