

# » C9350 BRAKE LATHE



## Main specifications

Spindle Travel	6.875" (175mm)	Spindle Speed	70,88,118 RPM
Spindle Feed Speed	0.002" (0.05mm)–0.02" (0.5mm) Rev	Cross Feed Speed	0.002" (0.05mm)–0.02" (0.5mm) Rev
Handwheel Graduations	0.002" (0.05mm)	Rotor Diameter	7" –15" (180–381mm)
Rotor Thickness	1.875" (48mm)	Drum Diameter	6" –17.7" (152–450mm)
Drum Depth	6.875" (175mm)	Motor	110V/220V/380V 50/60Hz
Gross Weight	290KG	Dimension	1010 × 950 × 1150mm

## Feature:

1. Quickly, accurately and efficiently cutting both drum and rotor.
2. Fast and slow setting.
3. Three kinds of speed to choose for spindle speed.
4. A convenient design to quickly change from rotor to drum.
5. Stop automatically after the cutting.



## Standard Adapter

No.	Description	Part No.	Qty.
1	Twin Cutter	C4-09-00	1
2	Arbor (1" /25.4mm) with nut, combination washer, flat washer and tie rod	C4-00-42/C4-00-48A/C4-05-00/C4-00-47	1
3	Plastic Safety Shield	C4-11-00	1
4	Open End Wrench (27–30mm)		1
5	Square Wrench		1
6	V Belt A610		1
7	Cutting Bar	C4-10-0C/C4-9-9-0C/C4-9-10-0C	3
8	Silencing Belt for Rotor and Drum	C4F-4-0 C4-12-0	2
9	Taper Cone (30x44mm)	C4-00-44-01 (For 1" Arbor)	1
10	Taper Cone (31x57mm)	C4-00-44-02 (For 1" Arbor)	1
11	Taper Cone (45x70mm)	C4-00-44-03 (For 1" Arbor)	1
12	Taper Cone (59x75mm)	C4-00-44-04 (For 1" Arbor)	1
13	Taper Cone (66x82mm)	C4-00-44-05 (For 1" Arbor)	1
14	Taper Cone (74x90mm)	C4-00-44-06 (For 1" Arbor)	1
15	Taper Cone (85.8x103mm)	C4-00-44-07 (For 1" Arbor)	1
16	Double Taper Cone 1.34" x1.66" (34x42mm)	C4-00-44-8	1
17	Double Taper Cone 1.36" x1.69" (35x43mm)	C4-00-44-9	1
18	Double Taper Cone 1.72" x2.06" (44x52mm)	C4-00-44-10	1
19	Double Taper Cone 2.06" x2.44" (52x62mm)	C4-00-44-11	1
20	Double Taper Cone 2.45" x2.81" (62x71mm)	C4-00-44-12	1
21	Spring	C4-00-45 (For 1" Arbor)	1
22	Clamp (94mm)	C4-00-46-01 (For 1" Arbor)	2
23	Clamp (116mm)	C4-00-46-02 (For 1" Arbor)	2
24	Clamp (146mm)	C4-00-46-03 (For 1" Arbor)	2