

ESW-806B+A350b CAR TYRE CHANGER



Enhanced base for column



Oil-water separator for exporting



Automatic working head



Three points tire pressing mechanical arm



Pendular shovel



Optional single intake cylinder



Features:

1. New design automatic working head instead of crowbar and equipped with plastic protective pad to double protect the rim from damage.
2. Adopt pneumatic locking device, operation easily and conveniently.
3. Wheel seat equip with nylon plate, can not damage the rim, suitable for many kinds of tyre.
4. Enhanced S41 hexagon shaft with better intensity to avoid mechanical deformation during working.
5. Base of mechanical arm is a complete one set, inside with wear-resistant macromolecule nylon slide block, to achieve smooth operating.
6. The structure design is novel, the layout is reasonable, in order to use more flexible and convenient.
7. Add three working pressure points to make mounting and demounting tyres are save time and labor, increase efficiency at the same time.

Technical parameter

Rim size	14" -28"	Complete machine packing size	1250x1050x1760mm
Max. wheel diameter	1180mm	Separated machine packing size	1250x920x1060mm
Max. tire width	3" -14"	Auxiliary hand packing size	1120x360x300mm
Working pressure	8-10bar	Net/Gross weight	336kg/378kg
Voltage	380V/220V/110V	Auxiliary hand weight	60kg
Power	0.75kW/1.1kW		