

ESW-806A+B350 CAR TYRE CHANGER



24" special designed working



Enhanced base



Enhanced bead breaker arm



Oil-water separator for exporting



Air inflation indicator+tool-box



Optional single intake cylinder



Features:

- 1.Enhanced S41 hexagon shaft with better intensity to avoid mechanical deformation during working.
- 2.Clamping jaw is equipped with a protective sleeve to provide more comprehensive protection for the tyres and rims.
- 3.Equipped with mechanical arm which makes mounting and demounting tire more quicker and easier.
- 4.The clamping jaw is made of precision steel cast which is firm and durable.
- 5.Base of mechanical arm is a complete one set, inside with wear-resistant macromolecule nylon slide block, to achieve smooth operating.
- 6.The structure design is novel, the layout is reasonable, in order to use more flexible and convenient.

Technical parameter

Rim clamp from outside	9" -21"	Power	0.75kW/1.1kW
Rim clamp from inside	13" -25"	Complete machine packing size	1150x1050x1760mm
Max. wheel diameter	1120mm	Separated machine packing size	1150x920x1060mm
Max. tire width	3" -14"	Auxiliary hand packing size	1120x300x360mm
Working pressure	8-10bar	Net/Gross weight	299kg/345kg
Voltage	380V/220V/110V	Auxiliary hand weight	60kg