

» C9372 BRAKE LATHE



Main specifications

Feed Rates—Rotor and Drum	0" -0.026" (0mm-0.66mm)	Spindle Speed	70-320RPM
Feed Rates Per Minute	2.54" (64.5mm)	Spindle Weight Capacity (Standard 1" Arbor)	150lbs(68Kg)
Flywheel Diameter	6" -24" (152-610mm)	Rotor Diameter	4" -20" (102-508mm)
Maximum Rotor Thickness	2.85" (73mm)	Drum Diameter	6" -19.5" (152-500mm)
Drum Depth	6.5" (165mm)	Motor	110V/220V 50/60Hz
Gross Weight	300KG	Dimension	1100 x 730 x 720mm

Feature:

1. High Efficiency---A convenient design allows to quickly change from rotor to drum.
2. Perfect Finish---The perfect finish meets or exceeds all OEM specifications.
3. Simple Convenience---A tool tray and top board means you can easy to take tools and adapters.
4. Infinitely Speed---Variable spindle speed and cross feed speed provide a perfect finish.
5. Single Pass---Positive rate tooling for optimum finish with a single pass.



Standard Adapter

No.	Description	Part No.	Qty.
1	Taper Cone (45x70mm)	C4-00-44-03 (For 1" Arbor)	1
2	Taper Cone (59x75mm)	C4-00-44-04 (For 1" Arbor)	1
3	Taper Cone (66x82mm)	C4-00-44-05 (For 1" Arbor)	1
4	Taper Cone (74x90mm)	C4-00-44-06 (For 1" Arbor)	1
5	Clamp (94mm)	C4-00-46-01 (For 1" Arbor)	2
6	Clamp (116mm)	C4-00-46-02 (For 1" Arbor)	2
7	Clamp (146mm)	C4-00-46-03 (For 1" Arbor)	2
8	Spring	C4-00-45 (For 1" Arbor)	1
9	Open End Wrench (27-30mm)		1
10	Silencing Belt for Rotor and Drum	C4F-4-0 C4-12-0	2
11	Spacer	For 1" Arbor	6
12	Hub Localize (Arbor 2" /50.8 mm)	C8F-01-01	1
13	Localizer Big Taper Cone (79x108mm)	C8F-01-02 (For 2" Arbor)	1
14	Localizer Small Taper Cone (54x82.5mm)	C8F-01-03 (For 2" Arbor)	1
15	Nut	C8F-01-04 (For 2" Arbor)	1
16	Big Spacer (171.5mm)	C8F-02(For 2" Arbor)	1
17	Small Spacer (133mm)	C8F-03(For 2" Arbor)	1
18	Big Adapter (171.5mm)	C8F-04-00 (For 2" Arbor)	1
19	Small Adapter (133mm)	C8F-05-00 (For 2" Arbor)	1
20	Step Adapter (25.4x50.8mm)	C8F-06 (For 2" Arbor)	1
21	Bend Wrench (78-85mm)		1