

Material Safety data sheet

QUICK DRING ADHESIVE B



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **DQ-TOOL® quick drying adhesive B**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC32 Polymer preparations and compounds
- **Process category**
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4 Chemical production where opportunity for exposure arises
PROC5 Mixing or blending in batch processes
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC10 Roller application or brushing
PROC13 Treatment of articles by dipping and pouring
PROC14 Tableting, compression, extrusion, pelletisation, granulation
- **Environmental release category**
ERC8c Widespread use leading to inclusion into/onto article (indoor)
ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- **Application of the substance / the mixture**
isocyanate component of a 2-component special resin system for industrial or professional applications
- **Applications, which are not recommended:** Not suitable for do-it-your-self-applications
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
Dongguan Dongquan Mould Materials Co., Ltd
ADD: No.10 Yihuan Road,Chiling Industrial,Dongguan City,CHINA
Email: dqtoolingboard@gmail.com
- **1.4 Emergency telephone number:** +86 0769-85878968

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Acute Tox. 4 H332 Harmful if inhaled.

(Contd. on page 2)

GB

Material Safety data sheet

(Contd. of page 1)

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

formaldehyde, oligomeric reaction product with aniline and phosgene (oligomeric MDI)

· **Hazard statements**

H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**

Danger for health when breathing in. Effect of sensitization on the lungs. Recognized allergen. Persons with hypersensitive respiratory tracts (asthma, chronic obstructive pulmonary) should not handle with the product.

(Contd. on page 3)

GB

Material Safety data sheet

(Contd. of page 2)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.1 Substances**
- **CAS No. Description**
- 7085-85-0 Ethyl cyanoacrylate 70-90%
- **CAS No. Description**
- 68410-23-1 Ethyl cyanoacrylate 10-30%
- Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Rinse with warm water.
Clean with water and soap. If possible, also wash with polyethylene glycol 400.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Information for doctor:**
The product irritates the respiratory tract and is a potential sensor for sensitization of skin and respiratory tract. The treatment of the acute irritation or bronchial constriction is primarily symptomatic. Depending on extent of the exposition and disturbances a longer medical care can be necessary.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
When fire carbon monoxide, nitrogen oxides, isocyanate vapours and traces of hydrogen cyanide can be developed.

(Contd. on page 4)

GB

Material Safety data sheet

(Contd. of page 3)

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

· Additional information

In case of flame spread pressure build-up, bursting danger. Containers should be cooled with water and removed from danger zone.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Final cleanup with following neutralizing agent: Mixture of water (90%), soda (8%) and liquid wetting agent (2%).

· 6.4 Reference to other sections

After approx. 1 hour to be filled in suitable barrels; the barrels should not be closed (liberation of CO₂), but only covered. They should be left outside for 7-14 days, then the containers can be disposed according to official regulations.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

The air limiting values mentioned in chapter 8 have to be controlled. At places of work, where aerosols and/or fumes can occur in higher concentrations, exceeding of limiting hygienic values has to be prevented by specific air exhaust. The air motions have to be carried out from the persons away.

The personal safety measures mentioned in chapter 8 are to be followed. The measures regarding handling with isocyanate are to be followed. Contact with skin and eyes as well as breathing in of vapours is to be avoided.

Safety precautions for handling of just molded polyurethane parts (prototypes, positives or negatives):

Depending on the production parameters, any uncovered surfaces of polyurethane moldings containing isocyanates as raw material, may contain traces of substances (e. g. primary and reaction products, catalysts, release agents) with hazardous characteristics. Avoid any skin contact with traces of

these substances! When demolding or otherwise handling just molded polyurethane parts, use protective nitrile rubber gloves (according to DIN EN 374) or protective nitrile rubber

(Contd. on page 5)

GB

Material Safety data sheet

(Contd. of page 4)

gloves against mechanic exposure. For any further skin protection we recommend to wear protective clothing when handling just molded polyurethane parts.

In case you are aware of any allergic reaction to this material, consult your company physician (in line with risk assessment) before working with the product.

- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from humidity and water.
Please stir or shake thoroughly before use!
Cooling-down below 10°C should be avoided.
Heating over 40°C should be avoided.
Keep container tightly closed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:** Not required.

· DNELs		
32055-14-4 formaldehyde, oligomeric reaction product with aniline and phosgene (oligomeric MDI)		
Oral	short term DNEL systemic effects	20 mg/kg (Consumer)
Dermal	short term systemic effects	25 mg/kg (Consumer)
		50 mg/kg (worker)
	short term local effects	17.2 mg/cm ² (Consumer)
		28.7 mg/cm ² (worker)
Inhalative	long term DNEL systemic effects	mg/kg (worker)
	long term DNEL local effects	mg/cm ² (worker)
	short term systemic effects	0.1 mg/m ³ (worker)
	short term local effects	0.1 mg/m ³ (worker)
	long term systemic effects	0.025 mg/m ³ (Consumer)
		0.05 mg/m ³ (worker)
	long term DNEL local effects	0.05 mg/m ³ (worker)
· PNECs		
32055-14-4 formaldehyde, oligomeric reaction product with aniline and phosgene (oligomeric MDI)		
NOEC (seedling emergence)	>1,000 mg/kg (<i>Lactuca sativa</i>) (OECD-Prüfrichtlinie 208)	
	>1,000 mg/kg (<i>Avena sativa</i> (Hafer)) (OECD-Prüfrichtlinie 208)	

(Contd. on page 6)

GB

Material Safety data sheet



(Contd. of page 5)

NOEC (21 d)	>10 mg/l (daphnia magna) (OECD-Prüfrichtlinie 202)
PNEC	>1 mg/l (Sediment) >0.1 mg/l (seawater) >1 mg/l (freshwater)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of exceeding the limit value.

Filter A2/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Protective gloves

For the permanent contact gloves made of Nitrilkautschuk with a layer thickness of at least 0.40 mm are suitable. The penetration time of this glove material is 480 minutes.

The glove material has to be according the requirement of EU-guideline 89/686/EWG and the resulting norm EN374, for example KCL Camatril Velour,0730. The above mentioned penetration times are based on laboratory measurements of KCL according to EN 374.

This recommendation is only valid for the product, which is delivered from us and only for the intended mentioned application. Regarding dissolution or mixing with other substances please contact suppliers of CE-approved gloves. (For example KCL GmbH, D-36124 Eichenzell, internet: www.kcl.de)

DQ gives this recommendation in good faith, without liability for any claims arising from the recommendation or the use of the suggested protection gloves.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

GB

(Contd. on page 7)

Material Safety data sheet

(Contd. of page6)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	light yellow
Odour:	Especial odor

· **pH-value at 20 °C:** < 7 (ISO 8975)

· **Change in condition**

Melting point/freezing point: 5 °C (EG A 1)
Initial boiling point and boiling range: > 300 °C (EG A 2)

· **Flash point:** > 200 °C (EG A 9)

· **Ignition temperature:** > 600 °C (EG A 15)

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Vapour pressure at 20 °C:** < 0.0009 Pa

· **Density at 20 °C:** 1.24 g/cm³ (ISO 2811)

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Viscosity:**

Dynamic at 20 °C: 120 mPas (DIN 53019)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

At approx. 200°C polymerization, CO₂-separation.

· **10.3 Possibility of hazardous reactions**

Contact with water releases gases (CO₂), polymerisation, danger of burst. Sometimes intensive reaction with bases as well as with several organic substances as alcohols and amines.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

Cyan hydrogen (HCN)

Possible in traces.

GB
(Contd. on page8)

Material Safety data sheet

(Contd. of page 7)

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**

· **Acute toxicity**

Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

32055-14-4 formaldehyde, oligomeric reaction product with aniline and phosgene (oligomeric MDI)		
Oral	LD50	>10,000 mg/kg (rat) (OECD-Guideline 401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD-Guideline 402)
Inhalative	LC50/4 h Aerosole	310 mg/l (Rat) (OECD-Prüfrichtlinie 403)
	LOAEL Langzeittoxizität	1 mg/m ³ (rat) (OECD-Prüfrichtlinie 453)
	NOAEL maternal	4 mg/m ³ (rat) (OECD-Prüfrichtlinie 414)
	NOAEL (carcinogenicity)	mg/l (rat) (OECD-Prüfrichtlinie 453)
	NOAEL (developmental toxicity)	4 mg/l (rat) (OECD-Prüfrichtlinie 414)
	NOAEL (teratogenicity)	12 mg/l (rat) (OECD-Prüfrichtlinie 414)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· **Additional toxicological information: sensitizing**

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity**

Suspected of causing cancer.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause respiratory irritation.

· **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

32055-14-4 formaldehyde, oligomeric reaction product with aniline and phosgene (oligomeric MDI)	
LC50 (96 h)	>1,000 mg/l (da) (OECD-Prüfrichtlinie 203)

(Contd. on page 9)

GB

Material Safety data sheet

(Contd. of page 8)	
<i>ErC50 (72 h)</i>	>1,640 mg/l (<i>Scenedesmus subspicatus</i>) (OECD-Prüfrichtlinie 201)
<i>EC 50 (3h)</i>	>100 mg/l (<i>activated sludge</i>) (OECD-Prüfrichtlinie 209)
<i>NOEC Mortalität</i>	>1,000 mg/kg (Reg) (OECD-Prüfrichtlinie 207)
<i>NOEC Wachstumsrate</i>	>1,000 mg/kg (<i>Lactuca sativa</i>) (OECD-Prüfrichtlinie 208)
<i>EC 50 (24 h)</i>	>1,000 mg/l (<i>daphnia magna</i>) (OECD-Prüfrichtlinie 202)
<ul style="list-style-type: none"> · 12.2 Persistence and degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. · Additional ecological information: · General notes: Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. · 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available. 	

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

<i>HP 4</i>	<i>Irritant - skin irritation and eye damage</i>
<i>HP 5</i>	<i>Specific Target Organ Toxicity (STOT)/Aspiration Toxicity</i>
<i>HP 7</i>	<i>Carcinogenic</i>
<i>HP 13</i>	<i>Sensitising</i>

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|------|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, ADN, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA | Void |

(Contd. on page 10)

GB

Material Safety data sheet

(Contd. of page 9)	
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class 	Void
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	Void
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · 14.6 Special precautions for user 	Not applicable.
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · IATA · Remarks: 	
<ul style="list-style-type: none"> · UN "Model Regulation": 	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3**
- **National regulations:**
- **VOC (EC) 0.00 %**

Class	Share in %
I	100.0

- **Waterhazard class:** Water hazard class 1 (Assessment by list): slightly hazardous for water.
- **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

Substance is not listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product Safety
- **Abbreviations and acronyms:**
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 11)

GB

Material Safety data sheet

--

(Contd. of page 10)

Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Annex: Exposure scenario

- **Short title of the exposure scenario**
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** *PC32 Polymer preparations and compounds*
- **Process category**
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4 Chemical production where opportunity for exposure arises
PROC5 Mixing or blending in batch processes
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC10 Roller application or brushing
PROC13 Treatment of articles by dipping and pouring
PROC14 Tableting, compression, extrusion, pelletisation, granulation
- **Environmental release category**
ERC8c Widespread use leading to inclusion into/onto article (indoor)
ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- **Notes** *The product is not intended for private use.*
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** *Usage only according to applications stated in the technical data sheets.*
- **Duration and frequency** *5 workdays/week.*
- **Worker** *4 hrs (half working shift).*
- **Physical parameters**
- **Physical state** *Fluid*
- **Concentration of the substance in the mixture** *Raw material.*
- **Used amount per time or activity** *Smaller than 100 g per application.*
- **Other operational conditions**
Observe the general safety regulations when handling chemicals.
- **Other operational conditions affecting environmental exposure**
No special measures required.
- **Other operational conditions affecting worker exposure**
Indoor application.
Outdoor application.
Avoid contact with eyes.
Avoid contact with the skin.
Avoid long-term or repeated skin contact.
Do not breathe gas/vapour/aerosol.

(Contd. on page 12)

GB

Material Safety data sheet

(Contd. of page 11)

- **Other operational conditions affecting consumer exposure**
Keep out of the reach of children.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
These measures are for all contributing scenarios at product temperatures BELOW 40 °C for pure MDI or BELOW 45 °C for other MDI based substances.
- **Organisational protective measures**
Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product.
Provide Internal Plant Instruction.
- **Technical protective measures**
A good general ventilation should be secured (not less than 3 to 5 air changes per hour).
In case of emission a exhaust device should be used.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Tightly sealed goggles
In case of exceeding the limit value.
Filter A2/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
In case of insufficient ventilation/ exhaust device at the working place a respiratory protective device with filter A /P2 should be use.
Protective gloves
For the permanent contact gloves made of Nitrilkautschuk with a layer thickness of at least 0.40 mm are suitable. The penetration time of this glove material is 480 minutes.
The glove material has to be according the requirement of EU-guideline 89/686/EWG and the resulting norm EN374, for example KCL Camatril Velour,0730. The above mentioned penetration times are based on laboratory measurements of KCL according to EN 374.

This recommendation is only valid for the product, which is delivered from us and only for the intended mentioned application. Regarding dissolution or mixing with other substances please contact suppliers of CE-approved gloves. (For example KCL GmbH, D-36124 Eichenzell, internet: www.kcl.de)

DQ gives this recommendation in good faith, without liability for any claims arising from the recommendation or the use of the suggested protection gloves.
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water**
Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
- **Disposal measures** Ensure that waste is collected and contained.

(Contd. on page 13)

GB

Material Safety data sheet

(Contd. of page 12)

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type *Partially emptied and uncleaned packaging*

· Exposure estimation**· Worker (inhalation)**

Contributory scenario: PROC2

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data

Evaluation type: short-term, inhalative

exposure grade: 0.026 mg/m³

risk ratio (exposure value/DNEL): 0.260

Contributory scenario: PROC3

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data.

Type of evaluation: short-term, inhalative

Grade of exposure: 0.018 mg/m³

Risk ratio (value of exposure/DNEL):0.184

Contributory scenario: PROC4

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data

Evaluation type: short-term, inhalative

exposure grade: 0.012 mg/m³

risk ratio (exposure value/DNEL): 0.116

Contributory scenario: PROC5

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data

Evaluation type: short-term, inhalative

exposure grade: 0.058 mg/m³

risk ratio (exposure value/DNEL): 0.582

Contributory scenario: PROC8a

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data

Evaluation type: short-term, inhalative

exposure grade: 0.058 mg/m³

risk ratio (exposure value/DNEL): 0.582

Contributory scenario: PROC8b

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data

Evaluation type: short-term, inhalative

exposure grade: 0.058 mg/m³

risk ratio (exposure value/DNEL): 0.582

Contributory scenario: PROC10

Method of evaluation: Measured value

Specific conditions: LEV: included in measured data

Evaluation type: short-term, inhalative

exposure grade: 0.034 mg/m³

risk ratio (exposure value/DNEL): 0.328

Contributory scenario: PROC13

Method of evaluation: Measured value

(Contd. on page 14)

GB

Material Safety data sheet

(Contd. of page 13)

*Specific conditions: LEV: included in measured data**Evaluation type: short-term, inhalative**exposure grade: 0.034 mg/m³**risk ratio (exposure value/DNEL): 0.344**Contributory scenario: PROC14**Method of evaluation: Measured value**Specific conditions: LEV: included in measured data**Evaluation type: short-term, inhalative**exposure grade: 0.012 mg/m³**risk ratio (exposure value/DNEL): 0.116**Contributory scenario: PROC2**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative**Grade of exposure: 0.013 mg/m³**Risk ratio (value of exposure/DNEL):0.260.**Contributory scenario: PROC3**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative**Grade of exposure: 0.009 mg/m³**Risk ratio (value of exposure/DNEL):0.038.**Contributory scenario: PROC4**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative**Grade of exposure: 0.006 mg/m³**Risk ratio (value of exposure/DNEL):0.116.**Contributory scenario: PROC5**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative**Grade of exposure: 0.029 mg/m³**Risk ratio (value of exposure/DNEL):0.582.**Contributory scenario: PROC8a**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative**Grade of exposure: 0.029 mg/m³**Risk ratio (value of exposure/DNEL):0.582.**Contributory scenario: PROC8b**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative**Grade of exposure: 0.029 mg/m³**Risk ratio (value of exposure/DNEL):0.582.**Contributory scenario: PROC10**Method of evaluation: Measured value**Specific conditons: LEV: included in measured data.**Type of evaluation: long-term, inhalative*

(Contd. on page 15)

GB

Material Safety data sheet

(Contd. of page 14)

Grade of exposure: 0.017 mg/m³
Risk ratio (value of exposure/DNEL):0.328.
Contributory scenario: PROC13
Method of evaluation: Measured value
Specific conditons: LEV: included in measured data.
Type of evaluation: long-term, inhalative
Grade of exposure: 0.017 mg/m³
Risk ratio (value of exposure/DNEL):0.344.
Contributory scenario: PROC14
Method of evaluation: Measured value
Specific conditons: LEV: included in measured data.
Type of evaluation: long-term, inhalative
Grade of exposure: 0.006 mg/m³
Risk ratio (value of exposure/DNEL):0.116.
· **Consumer** Not relevant for this Exposure Scenario.
· **Guidance for downstream users** No further relevant information available.

GB