



LED Warning light



Item no.SM-0607-18B

Function & performance	Parameters
Item no.	SM-0607-18A Steady Lighting Model SM-0607-18B Strobe Flashing Model (Show on)
Dimension	Ø55.0*70.5mm / D2.16" x H2.78" Inch External diameter Ø55.2 * H65mm, D2.17" x H2.56" Inch
Working voltage	12 - 36V DC
Theoretical power /Actual Power	10W / 7.2W
Led lamp chip	LED- 0.2W *9Pcs/Group, 36Pcs in total 4 Groups (2835 Color temperature 2700K)
Components material	Transparent housing: PC (Amber); Heat sink: aluminium; Base: ABS (Black);
Flash frequency	120times/min, (Optional: Strobe flashing model or steady on model)
Waterproof and Dustproof	IP65
Working temperature	-40°C- +65°C
Transient shock	75VDC, 20Ms
Reverse polarity protection	36VDC
Life span	25000h, Light attenuation≤15%, Working 8000h
Wiring method	External termianl DT04-2P + wire harness L300mm (The Length of wire accepted customized)
Installation method	Embedded, screw fixture, 2-M8*20, Distance of two mounting holes are 300mm
Application	Engineering vehicle、 Special vehicle、 Agriculture machinery
Packaging	White color box,1set/box, 12sets/carton (6 Pairs)