

LED Warning light

Item no. SM-1015-18J



Function and performance	Parameters
Item no.	SM-1015-18A Strobe Flashing Model SM-1015-18B Steady Lighting Model SM-1015-18J Sound & Light Combined Flashing Light (Show on)
Dimension	Ø96 * H159 mm / D3.78 " x H6.26" Inch
Working voltage	12-48V DC
Theoretical power	8W -Light , 3W -Sound, (LED chip -0.5W*48Pcs)
Components	Transparent housing: Optical PC, Amber color
	Mountingbase: PC Black, Strong magnetic
Color temperature(total)	2700K, Amber color (Base on CIE 1931 requirement)
Sound pressure	100 dB @1m
Working temperature	-40°C- +85°C
Waterproof and Dustproof	IP65
Corrosion resistance of surface	Neutral salt spray test 48H
Working temperature	-40°C- +85°C
Withstand voltage test	48VDC, 360S
Reverse polarity protection	48VDC, 60min
Life span	25000h
Regulation	GB 24965.2-2010
Wiring method	Intergrate DT with open wire, Red and Black cables, DT terminal DT04-3P (wire length as request)
Installation method	Strong magnet set up
Application	Engineering vehicle、 Agricultural machinery, Special vehicle
Packaging	White color box,1set/box, 18sets/carton (9 Pairs)