



# LED Cab light

## SM-1105-SFA



Function and performance	Parameters
Item no.	SM-1105-SFA
Dimension	L262 * W46 * T39.7 mm L10.31" x W1.81" x T1.56" Inch
Working voltage	12-36V DC
Theoretical power	10W, LED (2835) 0.5W*10Pcs Color temperature: 4000K, White color
Theoretical power / Actual power	5W / 4W LED -0.5W*10Pcs
Working temperature	-40°C- +85°C
Component	Lens: transparent PC (Matte and textured finish + Grey ABS); Base: ABS Black color
Over voltage protection	36VDC, 10min
Reverse polarity protection	36VDC, 60min
Life span	25000h, continuous working for 6000h, light attenuation is ≤20%
Connection	Direct wiring, wire length 150mm Black cable: negative pole; Red cable: positive pole
Installation method	Built-in install, mounting screw. Φ3.2 mounting hole, 212mm between two mounting holes
Application	Cab & Dashboard of engineering vehicle , Special vehicle, Agricultural machinery
Packaging	White color box, 1set/box, 80sets/carton (40 Pairs)

**SAMMOON VEHICLE LIGHTING TECHNOLOGY CO., LTD**

Add: 2nd-3rd Section, 4th Floor, Building 1, Hongxing Real Estate, No. 6, Foluo Road, Luocun, Shishan Town, Nanhai District, Foshan City, Guangdong province, China