

Headlight of Construction machinery

SM-12059-SDA



Function and performance	Parameters
Item No.	SM-12059-SDA
Function	Work light + Turn signals
Dimension	L318.4 * W139.2 * T71.4 (81.4) mm L12.54" x W5.48" x T2.81" Inch
Working voltage	Work light: 12-48V DC Turn signals: 24 V DC
Theoretical power/Actual power	Work light: 45W 3W*15Pcs, 3000-3800K, White color Turn signals: 14W 1W*14Pcs, 1500-3500 Amber color
Regulation	Work light: Flood (H45°, V35°)
Waterproof and Dustproof	IP67
Corrosion resistance of surface	Neutral salt spray test 72hours
Withstand voltage test	Work light: 48VDC, 60Min Turn signals: 28VDC, 60Min
Working temperature	-40°C ~ +65°C
Reverse polarity protection	24VDC, 1Min
Vibration strength	6G
Life span	25000h, Light attenuation < 10% for working 8000h
Weather resistance	GB/T 10485-2007, Rule: ECE R6
Connection	Open end wires, Length 250mm (accepted customized)
Installation method	Embedded, screw fixture, Distance of two mounting holes in width side 93mm, Length side 278mm
Application	Engineering vehicle, Agriculture machinery, Mine machinery
Packaging	White color box. 1 set/box, 8 sets/carton (4Pairs)